

## Safety data sheet

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1 PRODUCT IDENTIFIER

Product name

MITOFLEKS 500 mL

#### 1.2 RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST

Relevant identified uses

Marker.

Uses advised against

No information.

#### 1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Supplier

MITOL, tovarna lepil, d.o.o., Sežana  
Partizanska c. 78  
6210 Sežana, Slovenia  
+386 5 73 12 300 (8:00-16:00)  
lilijana.kocjan@mitol.si

#### 1.4 EMERGENCY TELEPHONE NUMBER

Emergency

112

Supplier

+386 5 73 12 300 (8:00-16:00)



<https://my.chemius.net/p/0K4PM1/en/pd/en>

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1 CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

Classification according to Regulation (EC) No 1272/2008 (CLP)

Aerosol 1; H222 Extremely flammable aerosol.  
Aerosol 1; H229 Pressurised container: May burst if heated.  
Eye Irrit. 2; H319 Causes serious eye irritation.  
STOT SE 3; H336 May cause drowsiness or dizziness.

#### 2.2 LABEL ELEMENTS

Labelling according to Regulation (EC) No 1272/2008 [CLP]



**Signal word: DANGER**

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
EUH066 Repeated exposure may cause skin dryness or cracking.  
P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE/doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.  
P501 Dispose of contents/container in accordance with national regulation.

Contains:

acetone  
ethyl acetate

#### 2.3 OTHER HAZARDS

PBT/vPvB

No information.

Endocrine disrupting properties

## Safety data sheet

No information.

### Additional information

No information.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 SUBSTANCES

For mixtures see 3.2.

### 3.2 MIXTURES

Name	CAS EC Index Reach	%	Classification according to Regulation (EC) No 1272/2008 (CLP)	Specific Conc. Limits	Notes for substances
isobutane	75-28-5 200-857-2 601-004-00-0 01-2119485395-27	25-50	Flam. Gas 1; H220 Press. Gas; H280	/	C, U
acetone	67-64-1 200-662-2 606-001-00-8 01-2119471330-49	25-50	Flam. Liq. 2; H225 / Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	/	/
propane	74-98-6 200-827-9 601-003-00-5 01-2119486944-21	10-25	Flam. Gas 1; H220 Press. Gas; H280	/	U
ethyl acetate	141-78-6 205-500-4 607-022-00-5	10-25	Flam. Liq. 2; H225 / Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	/	/

### Notes for substances

C	Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers.  In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
U	When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

## SECTION 4: FIRST AID MEASURES

### 4.1 DESCRIPTION OF FIRST AID MEASURES

# Safety data sheet

## General notes

Never give anything by mouth to an unconscious person. Place patient in recovery position and ensure airway patency. When in doubt or if feeling unwell seek medical assistance. Show the safety data sheet and label to the physician.

## Following inhalation

Remove patient to fresh air - move out of dangerous area. Keep at rest in a position comfortable for breathing. If symptoms develop and persist, seek medical attention. If breathing is irregular or respiratory arrest occurs provide artificial respiration. Seek medical help immediately. In case of unconsciousness bring patient into stable side position and seek medical attention.

## Following skin contact

Take off all contaminated clothing. Areas of the body that have come into contact with the product must be rinsed with water. If symptoms develop and persist, seek medical attention. Wash contaminated clothes and shoes before reuse.

## Following eye contact

Immediately flush eyes with running water, keeping eyelids apart. If irritation persists, seek professional medical attention.

## Following ingestion

Not likely. Accidental ingestion: Rinse mouth thoroughly with water. Do not induce vomiting! Immediately consult a doctor. Show the physician the safety data sheet or label.

## **4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED**

### Following inhalation

Vapours may cause drowsiness and dizziness. Excessive exposure to spray mist, fog, or vapours may cause respiratory irritation. Coughing, sneezing, nasal discharge, labored breathing.

### Following skin contact

Contact with skin may cause irritation (redness, itching). Repeated exposure may cause dry skin or cracked skin.

### Following eye contact

Causes severe eye irritation. Redness, tearing, pain.

### Following ingestion

Not likely. Accidental ingestion: May cause abdominal discomfort. May cause nausea/vomiting and diarrhea.

## **4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED**

Treat symptomatically.

## **SECTION 5: FIREFIGHTING MEASURES**

### **5.1 EXTINGUISHING MEDIA**

#### Suitable extinguishing media

Carbon dioxide. Dry chemical powder. Water spray. Alcohol resistant foam. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

#### Unsuitable extinguishing media

Full water jet.

### **5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE**

#### Hazardous combustion products

In case of a fire toxic gases can be generated; do not inhale gases/smoke. In the event of fire the following can be generated: carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>).

### **5.3 ADVICE FOR FIREFIGHTERS**

#### Protective actions

In case of fire do not breathe fumes/gases. Vapours can form explosive mixtures with air. Prolonged heating can cause an explosion. In case of fire aerosols can explode and be propelled to considerable distances in different directions. Cool containers at risk with water spray. If possible remove containers from endangered area. No action shall be taken involving any personal risk or without suitable training.

#### Special protective equipment for fire-fighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (EN 137).

#### Additional information

No information.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES**

#### For non-emergency personnel

#### Protective equipment

Use personal protective equipment (Section 8).

#### Precautionary measures

Ensure adequate ventilation. Keep away from sources of ignition and/or heat; No smoking!

#### Emergency procedures

# Safety data sheet

Evacuate the danger zone. Prevent access to unprotected personnel. Prevent access to unauthorised personnel. Avoid contact with skin, eyes and clothing. Do not breathe vapour or mist.

## For emergency responders

Use personal protective equipment.

## 6.2 ENVIRONMENTAL PRECAUTIONS

Do not allow product to reach water/drains/sewage systems or permeable soil. The product is an aerosol, which is why leakage of large amounts of product is not expected. If accidental large entry into water or ground occurs, inform responsible authorities.

## 6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

### For containment

Stem the spill if this does not pose risks.

### For cleaning up

Use spark-proof tools. Collect the spray cans and hand them over to an authorized waste disposal contractor. Release of liquid because of damaged aerosol can (release of large quantities): In case of bigger spill, dam the spillage, pump the liquid into appropriate labelled containers, absorb the residue with absorbent material and dispose of according to local regulations. Do not absorb spillage with sawdust or other combustible material. Dispose in accordance with applicable regulations (see Section 13).

### OTHER INFORMATION

No information.

## 6.4 REFERENCE TO OTHER SECTIONS

See also sections 8 and 13.

# SECTION 7: HANDLING AND STORAGE

## 7.1 PRECAUTIONS FOR SAFE HANDLING

### Protective measures

#### Measures to prevent fire

Ensure adequate ventilation. Protect from open fire and other sources of ignition or heat. Pressurized container; protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Vapours and air form explosive mixtures. Take precautionary measures against static discharges. Use spark-proof tools.

#### Measures to prevent aerosol and dust generation

Use general or local exhaust ventilation to prevent inhaling vapours and aerosols.

#### Measures to protect the environment

Avoid release to the environment.

#### Other measures

No information.

#### Advice on general occupational hygiene

Refer to instructions on label and regulations for safety and health at work. Wear suitable protective equipment; see Section 8. Consider measures required in Section 8 of this safety data sheet. Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Avoid contact with skin, eyes and clothes. Do not breathe vapours/mist.

## 7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

### Technical measures and storage conditions

Store in accordance with local regulations. Follow safe storage practices for packed compressed gas as described by the Compressed Gas Association or the relevant agency in the country where the product is used. Keep out of the reach of children. Keep away from food, drink and animal feeding stuffs. Keep in cool and well ventilated area. Keep in well closed containers. Keep away from sources of ignition - no smoking. Protect against heat and direct sunlight. Keep away from oxidising substances.

### Packaging materials

No information.

### Requirements for storage rooms and vessels

Do not store in unlabelled containers.

### Storage class

No information.

### Further information on storage conditions

No information.

## 7.3 SPECIFIC END USE(S)

### Recommendations

See identified uses in Section 1.2.

### Industrial sector specific solutions

No specific data available.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## Safety data sheet

### 8.1 CONTROL PARAMETERS

#### Occupational Exposure limit values

Name	mg/m <sup>3</sup>	ml/m <sup>3</sup>	Short-term value mg/m <sup>3</sup>	Short-term value ml/m <sup>3</sup>	Remark	Biological Tolerance Values
<b>Acetone (67-64-1)</b>	1210	500	3620	1500	/	/
<b>Ethyl acetate (141-78-6)</b>	734	200	1468	400	/	/

#### Information on monitoring procedures

BS EN 14042:2003 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 689:2018 Workplace exposure. Measurement of exposure by inhalation to chemical agents. Strategy for testing compliance with occupational exposure limit values. BS EN 482:2021 Workplace exposure. Procedures for the determination of the concentration of chemical agents. Basic performance requirements.

#### DNEL/DMEL values

##### For product

No information.

##### For components

Name	Type	Exposure route	exp. frequency	Remark	value
<b>acetone</b>	Worker	inhalation	long term systemic effects	/	1210 mg/m <sup>3</sup>
<b>acetone</b>	Worker	inhalation	long term local effects	/	2420 mg/m <sup>3</sup>
<b>acetone</b>	Worker	dermal	long term systemic effects	/	186 mg/kg bw/day
<b>acetone</b>	Consumer	inhalation	long term systemic effects	/	200 mg/m <sup>3</sup>
<b>acetone</b>	Consumer	dermal	long term systemic effects	/	62 mg/kg bw/day
<b>acetone</b>	Consumer	oral	long term systemic effects	/	62 mg/kg bw/day
<b>ethyl acetate</b>	Worker	inhalation	long term systemic effects	/	734 mg/m <sup>3</sup>
<b>ethyl acetate</b>	Worker	inhalation	short term systemic effects	/	1468 mg/m <sup>3</sup>
<b>ethyl acetate</b>	Worker	inhalation	long term local effects	/	734 mg/m <sup>3</sup>
<b>ethyl acetate</b>	Worker	inhalation	short term local effects	/	1468 mg/m <sup>3</sup>
<b>ethyl acetate</b>	Worker	dermal	long term systemic effects	/	63 mg/kg bw/day
<b>ethyl acetate</b>	Consumer	inhalation	long term systemic effects	/	367 mg/m <sup>3</sup>
<b>ethyl acetate</b>	Consumer	inhalation	short term systemic effects	/	734 mg/m <sup>3</sup>
<b>ethyl acetate</b>	Consumer	inhalation	long term local effects	/	367 mg/m <sup>3</sup>
<b>ethyl acetate</b>	Consumer	inhalation	short term local effects	/	734 mg/m <sup>3</sup>
<b>ethyl acetate</b>	Consumer	dermal	long term systemic effects	/	37 mg/kg bw/day

# Safety data sheet

Name	Type	Exposure route	exp. frequency	Remark	value
ethyl acetate	Consumer	oral	long term systemic effects	/	4.5 mg/kg bw/day

## PNEC values

### For product

No information.

### For components

Name	Exposure route	Remark	value
acetone	fresh water	/	10.6 mg/L
acetone	marine water	/	1.06 mg/L
acetone	water treatment plant	/	100 mg/L
acetone	fresh water sediment	dry weight	30.4 mg/kg
acetone	marine water sediment	dry weight	3.04 mg/kg
acetone	soil	dry weight	29.5 mg/kg
acetone	water, intermittent release	fresh water	21 mg/L
ethyl acetate	fresh water	/	0.24 mg/L
ethyl acetate	water, intermittent release	fresh water	1.65 mg/L
ethyl acetate	marine water	/	0.024 mg/L
ethyl acetate	water treatment plant	/	650 mg/L
ethyl acetate	fresh water sediment	dry weight	1.15 mg/kg
ethyl acetate	marine water sediment	dry weight	0.115 mg/kg
ethyl acetate	soil	dry weight	0.148 mg/kg
ethyl acetate	food chain	oral	0.2 mg/kg feed

## 8.2 EXPOSURE CONTROLS

### Appropriate engineering control

### Substance/mixture related measures to prevent exposure during identified uses

Handle in accordance with good industrial hygiene and safety practice. Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Avoid contact with skin, eyes and clothes. Do not breathe vapours/aerosols. Keep away from foodstuffs, beverages and feed. If technical measures to reduce workers' exposure are not sufficient, and the limit values of hazardous substances in the air are exceeded, it is necessary to use personal protective equipment.

### Structural measures to prevent exposure

No information.

### Organisational measures to prevent exposure

Remove all contaminated clothes immediately and wash them before reuse.

### Technical measures to prevent exposure

Provide good ventilation and local exhaust in areas with increased concentration.

### Personal protective equipment

#### Eye and face protection

Safety glasses with side protection (EN 166).

#### Hand protection

Protective gloves (EN 374). Observe the manufacturer's instructions regarding the use, storage, maintenance and replacement of gloves. In case of damage or at the first signs of wear and tear, change the gloves immediately. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. The penetration time is determined by the protective glove manufacturer and must be observed.

### Appropriate materials

#### Skin protection

Cotton protective clothing and shoes that cover the entire foot (EN ISO 20345). Protective antistatic clothing EN 1149 (1:2006, 2:1998 and 3:2004, 5:2008), protective antistatic shoes (EN 20345:2012). Choose body protection according to the activity and possible exposure.

#### Respiratory protection

In case of insufficient ventilation wear suitable respiratory protection. If the concentration limit values are exceeded, it is necessary to wear appropriate respiratory protection. Wear suitable protective breathing mask (BS EN 136) with filter A2-P2 (BS EN 14387).

#### Thermal hazards

# Safety data sheet

No information.

Environmental exposure controls

Substance/mixture related measures to prevent exposure

No information.

Instruction measures to prevent exposure

No information.

Organisational measures to prevent exposure

No information.

Technical measures to prevent exposure

No information.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Physical state

liquid - aerosol

Colour

green

Odour

characteristic

Important health, safety and environmental information

<b>Odour threshold</b>	No information.
<b>Melting point/Freezing point</b>	No information.
<b>Boiling point or initial boiling point and boiling range</b>	No information.
<b>Flammability</b>	No information.
<b>Lower and upper explosion limit</b>	1.5 — 10.9 vol % (propellant) 2.1 — 13 vol % (acetone)
<b>Flash point</b>	No information.
<b>Auto-ignition temperature</b>	No information.
<b>Decomposition temperature</b>	No information.
<b>pH</b>	No information.
<b>Viscosity</b>	No information.
<b>Solubility</b>	No information.
<b>Partition coefficient</b>	No information.
<b>Vapour pressure</b>	240 hPa at 20 °C
<b>Density and/or relative density</b>	Density: 0.963 kg/L at 20 °C (data refers to the liquid portion of the product)
<b>Relative vapour density</b>	No information.
<b>Particle characteristics</b>	No information.

### 9.2 OTHER INFORMATION

<b>Weight organic solvents</b>	622 g/l (VOC) 89 % (VOC)
<b>Explosive properties</b>	Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 REACTIVITY

Stable under recommended transport or storage conditions.

### 10.2 CHEMICAL STABILITY

Product is stable under normal conditions of use, recommended handling and storage conditions.

### 10.3 POSSIBILITY OF HAZARDOUS REACTIONS

## Safety data sheet

The product is stable under recommended storage and handling conditions. Vapours and air can form flammable or explosive mixtures.

### 10.4 CONDITIONS TO AVOID

Avoid all possible sources of ignition (spark or flame). Do not expose to heat and direct sunlight. Do not store above 50°C.

### 10.5 INCOMPATIBLE MATERIALS

Oxidants.  
Peroxide.

### 10.6 HAZARDOUS DECOMPOSITION PRODUCTS

Under normal use conditions no hazardous decomposition products are expected. In case of fire/explosion vapours/gases that pose a health hazard are released. Carbon dioxide; Carbon monoxide.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1 INFORMATION ON HAZARD CLASSES AS DEFINED IN REGULATION (EC) NO 1272/2008

#### (a) Acute toxicity

For components

Name	Exposure route	Type	Species	Time	value	Method	Remark
acetone	inhalation	LC <sub>50</sub>	rat	4 h	ca. 76 mg/l	/	/
acetone	dermal	LD <sub>50</sub>	rabbit	/	> 15800 mg/kg	/	/
acetone	oral	LD <sub>50</sub>	rat	/	5800 mg/kg	OECD 401	/
ethyl acetate	oral	LD <sub>50</sub>	rabbit	/	5620 mg/kg	/	/
ethyl acetate	inhalation	LC <sub>50</sub>	rat	4 h	1600 mg/l	/	/

#### Additional information

The product is not classified for acute toxicity.

#### (b) Skin corrosion/irritation

For components

Name	Species	Time	result	Method	Remark
acetone	guinea pig	/	Non-irritant.	/	/

#### Additional information

The product is not classified as irritating to the skin.

#### (c) Serious eye damage/irritation

For components

Name	Exposure route	Species	Time	result	Method	Remark
acetone	/	rabbit	/	Irritating to eyes.	OECD 405	/
acetone	/	rabbit	/	Irritates the eyes. The occurrence of corneal injuries is possible.	OECD 405	/

#### Additional information

Causes serious eye irritation.

#### (d) Respiratory or skin sensitisation

For components

Name	Exposure route	Species	Time	result	Method	Remark
------	----------------	---------	------	--------	--------	--------



## Safety data sheet

Name	Exposure route	Species	Time	result	Method	Remark
acetone	-	guinea pig	/	Non sensitising.	OECD 406	/

### Additional information

The product is not classified as sensitising.

### (e) (Germ cell) mutagenicity

#### For product

Type	Species	Time	result	Method	Remark
/	/	/	The chemical is not classified as mutagenic.	/	/

#### For components

Name	Type	Species	Time	result	Method	Remark
acetone	/	Bacteria	/	The tests did not show mutagenic effects	/	/
acetone	/	Cell: Mammalian-Animal	/	The tests did not show mutagenic effects	/	/
acetone	in-vitro mutagenicity	/	/	Negative.	OECD 473	Chromosome aberration assay
acetone	in-vitro mutagenicity	Cell: Mammalian-Animal	/	Negative.	OECD 476	/
acetone	in-vitro mutagenicity	Bacteria	/	Negative.	OECD 471	/
acetone	in-vivo mutagenicity	mouse	/	Negative.	The micronucleus test	/

### (f) Carcinogenicity

#### For product

Exposure route	Type	Species	Time	value	result	Method	Remark
/	/	/	/	/	The chemical is not classified as carcinogenic.	/	/

#### For components

Name	Exposure route	Type	Species	Time	value	result	Method	Remark
acetone	/	/	/	/	/	Animal testing did not show any carcinogenic effects.	/	/
acetone	dermal	/	mouse	/	/	negative	/	/

## Safety data sheet

### (g) Reproductive toxicity

#### For product

Reproductive toxicity type	Type	Species	Time	value	result	Method	Remark
/	/	/	/	/	The chemical is not classified as toxic for reproduction.	/	/

#### For components

Name	Reproductive toxicity type	Type	Species	Time	value	result	Method	Remark
acetone	Reproductive toxicity	/	/	/	/	Animal testing did not show any effects on fertility.	/	/
acetone	Teratogenicity	/	rat	/	/	Negative.	OECD 414	/

### Summary of evaluation of the CMR properties

The product is not classified as carcinogenic, mutagenic or toxic for reproduction.

### (h) STOT-single exposure

#### For components

Name	Exposure route	Type	Species	Time	Exposure organ	value	result	Method	Remark
acetone	-	-	/	/	/	/	May cause drowsiness or dizziness.	/	/

### Additional information

May cause drowsiness or dizziness.

### (i) STOT-repeated exposure

#### For components

Name	Exposure route	Type	Species	Time	Exposure organ	value	result	Method	Remark
acetone	dermal	-	/	/	/	/	Repeated exposure may cause dry and cracked skin.	/	/
acetone	Repeated dose toxicity	NOAEL	rat	90 days	/	oral	900 mg/kg bw/day	/	/
acetone	Repeated dose toxicity	NOAEC	rat	/	/	/	22500 mg/m <sup>3</sup>	/	inhalation

## Safety data sheet

Name	ExposureType route	Species	Time	Exposure organ	value	result	Method	Remark
acetone	inhalation -	human	/	/	/	Headache, dizziness, fatigue, nausea and vomiting.	/	excessive exposure to vapors
acetone	dermal -	human	/	/	/	Repeated or prolonged exposure may cause dermatitis.	/	/
acetone	inhalation -	human	/	chronic	Nasal inner lining	Symptoms: inflammation of the mucous membranes.	/	/

### Additional information

Repeated exposure may cause skin dryness or cracking. STOT RE (repeated exposure): Not classified.

### (j) Aspiration hazard

No information.

### Additional information

Aspiration hazard: Not classified.

### Symptoms related to the physical, chemical and toxicological characteristics

No information.

### Interactive effects

No information.

## 11.2 INFORMATION ON OTHER HAZARDS

### Endocrine disrupting properties

No information.

### Other information

No information.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1 TOXICITY

#### Acute (short-term) toxicity

#### For components

Name	Type	value	Exposure time	Species	organism	Method	Remark
acetone	LC <sub>50</sub>	5540 mg/L	96 h	fish	<i>Oncorhynchus mykiss</i>	/	/
acetone	LC <sub>50</sub>	11000 mg/L	96 h	fish	<i>Alburnus alburnus</i>	/	/
acetone	LC <sub>50</sub>	8800 mg/L	48 h	crustacea	<i>Daphnia magna</i>	/	/
acetone	NOEC	430 mg/L	96 h	fish	/	/	/

## Safety data sheet

Name	Type	value	Exposure time	Species	organism	Method	Remark
------	------	-------	---------------	---------	----------	--------	--------

acetone	EC <sub>12</sub>	1000 mg/L	30 min	bacteria	Activated sludge	OECD 209	/
---------	------------------	-----------	--------	----------	------------------	----------	---

Chronic (long-term) toxicity

For components

Name	Type	value	Exposure time	Species	organism	Method	Remark
acetone	NOEC	2212 mg/l	28 days	crustacea	<i>Daphnia pulex</i>	/	reproduction

### 12.2 PERSISTENCE AND DEGRADABILITY

Abiotic degradation, physical- and photo-chemical elimination

For components

Name	Environment	Type / Method	Half Time	Evaluation	Method	Remark
acetone	water	/	/	Degraded by hydrolysis.	/	/

Biodegradation

For components

Name	Type	Rate	Time	Evaluation	Method	Remark
acetone	biodegradability	91 %	28 days	readily biodegradable	OECD 301 B	/
acetone	BOD	1900 mg/g	5 days	/	/	/
acetone	COD	2100 mg/g	/	/	/	/

### 12.3 BIOACCUMULATIVE POTENTIAL

Partition coefficient

For components

Name	Media	value	Temperature °C	pH	Concentration	Method
acetone	log Kow	-0.24	/	/	/	/

Bioconcentration factor (BCF)

For components

Name	Species	organism	value	Duration	Evaluation	Method	Remark
acetone	BCF	/	< 10	/	/	/	/

### 12.4 MOBILITY IN SOIL

Known or predicted distribution to environmental compartments

No information.

Surface tension

No information.

Adsorption/Desorption

No information.

### 12.5 RESULTS OF PBT AND VPVB ASSESSMENT

No evaluation.

### 12.6 ENDOCRINE DISRUPTING PROPERTIES

No information.

### 12.7 OTHER ADVERSE EFFECTS

No information.

### 12.8 ADDITIONAL INFORMATION

## Safety data sheet

### For product

Product is not classified as dangerous for environment. Water hazard class 1 (self-assessment): slightly hazardous for water. Avoid release to the environment.

### For components

#### acetone

Does not bioaccumulate. The substance is highly volatile. This substance is not considered to be persistent, bioaccumulative and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulative (vPvB). Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1 WASTE TREATMENT METHODS

#### Product / Packaging disposal

#### Waste chemical

Dispose of in accordance with applicable waste disposal regulation. Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste. Avoid release to the environment. Product and container must be disposed of safely.

#### Waste codes / waste designations according to LoW

16 05 04\* - gases in pressure containers (including halons) containing dangerous substances

#### Packaging

Dispose of in accordance with applicable waste disposal regulation. Deliver completely emptied containers to approved waste disposal authorities. Uncleaned containers should not be perforated, cut or welded. Pressurized container. Do not pierce or burn, even after use.

#### Waste codes / waste designations according to LoW

15 01 11\* - metallic packaging containing a dangerous solid porous matrix (for example asbestos), including empty pressure containers

#### Waste treatment-relevant information

No information.





#### Sewage disposal-relevant information

No information.

#### Other disposal recommendations

No information.

## SECTION 14: TRANSPORT INFORMATION

ADR/RID	IMDG	IATA	ADN
<b>14.1 UN number or ID number</b>			
UN 1950	UN 1950	UN 1950	UN 1950
<b>14.2 UN proper shipping name</b>			
AEROSOLS	AEROSOLS	AEROSOLS	AEROSOLS
<b>14.3 Transport hazard class(es)</b>			
2	2	2	2
			
<b>14.4 Packing group</b>			
Not given/not applicable	Not given/not applicable	Not given/not applicable	Not given/not applicable
<b>14.5 Environmental hazards</b>			
NO	NO	NO	NO
<b>14.6 Special precautions for user</b>			

## Safety data sheet

ADR/RID	IMDG	IATA	ADN
Limited quantities 1 L Special provisions 190, 327, 344, 625 Packing Instructions P207, LP200 Special packing provisions PP87, RR6, L2 Transport category 2 Tunnel restriction code (D)	Limited quantities 1 L EmS F-D, S-U	Limited Quantity, Packing Instructions (Ltd Qty, Pkg Inst) Y203 Limited Quantity, Maximum Net Quantity/Package (Ltd Qty, Max Net Qty/Pkg) 30 kg G Packing Instructions (Pkg Inst) 203 Maximum Net Quantity/Package (Max Net Qty/Pkg) 25 kg Special provisions A145, A167, A802	Limited quantities 1 L
<b>14.7 Maritime transport in bulk according to IMO instruments</b>	Goods may not be carried in bulk in bulk containers, containers or vehicles.		

## SECTION 15: REGULATORY INFORMATION

### 15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE

- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (including last amendment Commission Regulation (EU) 2020/878)
- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-guideline)

not applicable

Regulation EC 648/2004 on detergents

No information.

Special instructions

Water hazard class 1 (self-assessment): slightly hazardous for water.

### 15.2 CHEMICAL SAFETY ASSESSMENT

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## SECTION 16: OTHER INFORMATION

Indication of changes

2.2 Label elements 8.2 Exposure controls 9.1 Information on basic physical and chemical properties

Key literature references and sources for data

No information.

Abbreviations and acronyms

# Safety data sheet

---

**ATE - Acute Toxicity Estimate**

ADR - Agreement concerning the International Carriage of Dangerous Goods by Road

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

CEN - European Committee for Standardisation

C&amp;L - Classification and Labelling

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

CAS# - Chemical Abstracts Service number

CMR - Carcinogen, Mutagen, or Reproductive Toxicant

CSA - Chemical Safety Assessment

CSR - Chemical Safety Report

DMEL - Derived Minimal Effect Level

DNEL - Derived No Effect Level

DPD - Dangerous Preparations Directive 1999/45/EC

DSD - Dangerous Substances Directive 67/548/EEC

DU - Downstream User

EC - European Community

ECHA - European Chemicals Agency

EC-Number - EINECS and ELINCS Number (see also EINECS and ELINCS)

EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway)

EEC - European Economic Community

EINECS - European Inventory of Existing Commercial Substances

ELINCS - European List of notified Chemical Substances

EN - European Standard

EQS - Environmental Quality Standard

EU - European Union

Euphrac - European Phrase Catalogue

EWC - European Waste Catalogue (replaced by LoW – see below)

GES - Generic Exposure Scenario

GHS - Globally Harmonized System

IATA - International Air Transport Association

ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG - International Maritime Dangerous Goods

IMSBC - International Maritime Solid Bulk Cargoes

IT - Information Technology

IUCLID - International Uniform Chemical Information Database

IUPAC - International Union for Pure Applied Chemistry

JRC - Joint Research Centre

Kow - octanol-water partition coefficient

LC50 - Lethal Concentration to 50 % of a test population

LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose)

LE - Legal Entity

LoW - List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)

LR - Lead Registrant

M/I - Manufacturer / Importer

MS - Member States

MSDS - Material Safety Data Sheet

OC - Operational Conditions

OECD - Organization for Economic Co-operation and Development

OEL - Occupational Exposure Limit

OJ - Official Journal

OR - Only Representative

OSHA - European Agency for Safety and Health at work

PBT - Persistent, Bioaccumulative and Toxic substance

PEC - Predicted Effect Concentration

PNEC(s) - Predicted No Effect Concentration(s)

PPE - Personal Protection Equipment

(Q)SAR - Qualitative Structure Activity Relationship

REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006

RID - Regulations concerning the International Carriage of Dangerous Goods by Rail

RIP - REACH Implementation Project

RMM - Risk Management Measure

SCBA - Self-Contained Breathing Apparatus

SDS - Safety data sheet

SIEF - Substance Information Exchange Forum

SME - Small and Medium sized Enterprises

STOT - Specific Target Organ Toxicity

(STOT) RE - Repeated Exposure

(STOT) SE - Single Exposure

SVHC - Substances of Very High Concern

UN - United Nations

vPvB - Very Persistent and Very Bioaccumulative

**List of relevant H phrases**

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.