

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. PRODUCT IDENTIFIER

Product name

PARKETOLIT 1549B



chemius.net/eDXbc

1.2. RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST

Relevant identified uses

Hardener

Uses advised against

No information.

1.3. DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Manufacturer

MITOL, tovarna lepil, d.o.o., Sežana
Address: Partizanska c. 78 Sežana, Slovenia
Phone: +386 5 73 12 300
Fax: +386 5 73 12 390
E-mail: lilijana.kocjan@mitol.si
Point of contact for safety info: Lilijana Kocjan Žorž

1.4. EMERGENCY TELEPHONE NUMBER

112

+386 5 73 12 300 (8:00-16:00)

SECTION 2. HAZARDS IDENTIFICATION

2.1 CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

Classification according to Regulation (EC) No 1272/2008 (CLP)

Skin Irrit. 2; H315 Causes skin irritation.
Skin Sens. 1; H317 May cause an allergic skin reaction.
Eye Irrit. 2; H319 Causes serious eye irritation.
Acute Tox. 4; H332 Harmful if inhaled.
Resp. Sens. 1; H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
STOT SE 3; H335 May cause respiratory irritation.
Carc. 2; H351 Suspected of causing cancer.
STOT RE 2; H373 May cause damage to organs through prolonged or repeated inhalation.

SAFETY DATA SHEET

2.2 LABEL ELEMENTS

2.2.1. Labelling according to Regulation (EC) No 1272/2008 [CLP]



Signal word: **Danger**

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated inhalation.

P102 Keep out of reach of children.

P260 Do not breathe vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 In case of inadequate ventilation wear respiratory protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P311 IF exposed or concerned: Call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with national regulation.

2.2.2. Contains:

polymeric MDI (CAS: 9016-87-9)

'4,4'-methylenediphenyl diisocyanate (CAS: 101-68-8, EC: 202-966-0, Index: 615-005-00-9)

reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate (EC: 905-806-4)

2.2.3. Special provisions

MDI notice

Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

As from 24 August 2023 adequate training is required before industrial or professional use.

2.3. OTHER HAZARDS

Persons who have problems with sensitivity of the airways (asthma, chronic bronchitis), should avoid contact with the product.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Product description

Polymer.

3.1. SUBSTANCES

For mixtures see 3.2.

SAFETY DATA SHEET

3.2. MIXTURES

Name	CAS EC Index	%	Classification according to Regulation (EC) No 1272/2008 (CLP)	Specific Conc. Limits	REACH Registration No.
polymeric MDI	9016-87-9 - -	60-100	Skin Irrit. 2; H315 Skin Sens. 1; H317 Eye Irrit. 2; H319 Acute Tox. 4; H332 Resp. Sens. 1; H334 STOT SE 3; H335 Carc. 2; H351 STOT RE 2; H373		-
'4,4'-methylenediphenyl diisocyanate [C]	101-68-8 202-966-0 615-005-00-9	30-60	Skin Irrit. 2; H315 Skin Sens. 1; H317 Eye Irrit. 2; H319 Acute Tox. 4; H332 Resp. Sens. 1; H334 STOT SE 3; H335 Carc. 2; H351 STOT RE 2; H373	Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0,1 % STOT SE 3; H335: C ≥ 5 %	01-2119457014-47
reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate [C]	- 905-806-4 -	0,1-<1	Skin Irrit. 2; H315 Skin Sens. 1; H317 Eye Irrit. 2; H319 Acute Tox. 4; H332 Resp. Sens. 1; H334 STOT SE 3; H335 Carc. 2; H351 STOT RE 2; H373	Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0,1 % STOT SE 3; H335: C ≥ 5 %	01-2119457015-45

Notes for substances:

C	Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
----------	---

SECTION 4. FIRST AID MEASURES

4.1. DESCRIPTION OF FIRST AID MEASURES

General notes

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Never give anything by mouth to an unconscious person. Place patient in recovery position and ensure airway patency. Symptoms of poisoning may even occur after several hours; therefore medical observation is required at least 48 hours after the event.

No action shall be taken involving any personal risk or without suitable training.

Following inhalation

Remove patient to fresh air - move out of dangerous area. If victim is not breathing give artificial respiration. In case of difficulty breathing, give oxygen to the victim. Seek medical help immediately.

SAFETY DATA SHEET

Following skin contact

Immediately remove contaminated clothing. Wash affected skin areas thoroughly with plenty of water and soap. Rinse with a polyglycol-based skin cleanser or corn oil. If symptoms develop and persist, seek medical attention. Wash contaminated clothes and shoes before reuse.

Following eye contact

Immediately flush eyes with plenty of water while keeping eyelids apart (at least 15 minutes). After 5 minutes of rinsing, remove contact lenses, if present, and continue rinsing. If irritation persists, seek professional medical attention.

Following ingestion

Do not induce vomiting without prior consultation with a doctor. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. In case of doubt or if feeling unwell seek medical help.

4.2. MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

Inhalation

Harmful.
Irritating to respiratory system.
Causes irritation of nose and throat.
Coughing, sneezing, nasal discharge, labored breathing.
Feeling of tightness in the chest and dry throat.
Asthmatic problems.
Can cause sensitization.
Prolonged inhalation of vapours can cause lung injury.
The symptoms may be delayed and can subsequently occur several hours after the exposure.
By inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need 48-hour medical observation.

Skin contact

Irritating to the skin.
Itching, redness, pain.
May cause sensitisation by skin contact (symptoms: itching, redness, rashes).

Eye contact

Irritates the eyes.
Redness, tearing, pain.

Ingestion

May cause nausea/vomiting and diarrhea.
May cause abdominal discomfort.
Irritates mucous membranes in the mouth, throat, esophagus and in gastrointestinal area.

4.3. INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

Treat symptomatically. Symptoms of poisoning may appear several hours later. Keep under medical supervision for at least 48 hours.

SECTION 5. FIREFIGHTING MEASURES

5.1. EXTINGUISHING MEDIA

Suitable extinguishing media

Foam.
Carbon dioxide (CO₂).
Fire extinguishing powder.

Unsuitable extinguishing media

Full water jet. Water. The reaction between water and hot isocyanates may be dangerous.

SAFETY DATA SHEET

5.2. SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

Hazardous combustion products

In case of heating harmful vapours/gases can be generated. In the event of fire the following can be generated: carbon monoxide (CO), carbon dioxide (CO₂), Nitrogen oxides (NO_x).

5.3. ADVICE FOR FIREFIGHTERS

Protective actions

In case of fire or heating do not breathe fumes/vapours. In case of fire evacuate the area. Remove people from the area of fire and away from windows. No action shall be taken involving any personal risk or without suitable training. Cool containers at risk with water spray. If possible remove containers from endangered area. The reaction with water produces CO₂, which can cause a dangerous increase in pressure, if contaminated containers are closed again. Closed containers may explode if they are overheated.

Special protective equipment for firefighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (EN 137).

Additional information

Contaminated firefighting water must be disposed of in accordance with the regulations; do not allow to reach the sewage system. Contaminated firefighting water and fire residues must be disposed of in accordance with the local regulations.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

6.1.1. For non-emergency personnel

Protective equipment

Use personal protective equipment (Section 8). In case of insufficient ventilation, use respiratory protection equipment.

Emergency procedures

Ensure adequate ventilation. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Prevent access to unprotected personnel. Prevent access to unauthorised personnel. Do not touch or walk through spilled material. Do not breathe vapour or mist. Ensure good ventilation. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Use personal protective equipment.

6.2. ENVIRONMENTAL PRECAUTIONS

Do not allow product to reach water/drains/sewage systems or permeable soil. If accidental large entry into water or ground occurs, inform responsible authorities.

6.3. METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

6.3.1. For containment

Dam the spillage.

6.3.2. For cleaning up

Stop leak if without risk. Move containers from spill area. Absorb product (with inert material), collect it in special container and dispose it to a licensed hazardous-waste disposal contractor. Large spill: In case if product is in solid state: Vacuum or sweep up the material and place it in a designated, labeled waste container. If the formulation is in a liquid state: Absorb spilled quantities with suitable inert materials. Leave to react for at least 30 minutes. Do not absorb spillage with sawdust or other combustible material. Collect in a suitable container and dispose in accordance with the methods under Section 13. Rinse contaminated area with water! Test for isocyanate vapours before allowing personnel into the area. Neutralize the product (with decontaminative solution), Cover the spillage with decontamination solution for isocyanates (90% water, 8% ammonia, 2% detergent) and leave 10 minutes to react or pour with water and leave more than 30 minutes to react. The contaminated area should be cleaned with the following solution: 5% -10% sodium carbonate and 0,2-2% of liquid soap in water. Gather waste for destruction as hazardous waste.

SAFETY DATA SHEET

6.3.3. Other information

-

6.4. REFERENCE TO OTHER SECTIONS

See also Sections 8 and 13.

SECTION 7. HANDLING AND STORAGE

7.1. PRECAUTIONS FOR SAFE HANDLING

7.1.1. Protective measures

Measures to prevent fire

Ensure adequate ventilation.

Measures to prevent aerosol and dust generation

-

Measures to protect the environment

-

7.1.2. Advice on general occupational hygiene

Use personal protective equipment. Persons with a history of skin sensitisation problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before using. Do not use until you understand all safety precautions. Avoid contact with skin, eyes and clothes. Do not breathe vapours/mist. Product is not for eating – do not ingest! Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory protection equipment. Do not eat, drink or smoke while working. Before entering the dining room it is necessary to replace contaminated clothing. Use good personal hygiene practices – wash hands at breaks and when done working with material. Remove contaminated clothes and wash them before reuse. People with sensitive skin should not come into contact with the product.

7.2. CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

7.2.1. Technical measures and storage conditions

Store in accordance with local regulations. Keep in tightly closed container. Storage temperature 4-49°C. Store in a dry, cool and well-ventilated area, away from incompatible materials. Protect from direct sunlight. Keep away from food, drink and animal feeding stuffs. Keep in a locked place.

7.2.2. Packaging materials

The original container of producer. Keep in containers of the same material as the original one.

7.2.3. Requirements for storage rooms and vessels

The empty containers contain the residues of the preparation and therefore can also pose a risk. Close opened containers after use. Put the containers upright to prevent from leaking. Do not store in unlabelled containers. Use appropriate container to avoid environmental contamination.

7.2.4. Storage class

-

7.2.5. Further information on storage conditions

-

7.3. SPECIFIC END USE(S)

Recommendations

Empty packaging is not suitable for reuse. Do not use compressed air during filling, emptying or handling.

Industrial sector specific solutions

-

SAFETY DATA SHEET

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. CONTROL PARAMETERS

8.1.1. Occupational exposure limit values

No information.

8.1.2. Information on monitoring procedures

BS EN 14042:2003 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 482:2012+A1:2015 Workplace exposure. General requirements for the performance of procedures for the measurement of chemical agents. BS EN 689:2018 Workplace exposure. Measurement of exposure by inhalation to chemical agents. Strategy for testing compliance with occupational exposure limit values.

8.1.3. DNEL/DMEL values

For components

Name	Type	Exposure route	Exposure frequency	Value	Remark
'4,4'-methylenediphenyl diisocyanate (101-68-8)	Worker	dermal	short term (systemic effects)	50 mg/kg bw/day	
'4,4'-methylenediphenyl diisocyanate (101-68-8)	Worker	inhalation	short term (systemic effects)	0,1 mg/m ³	
'4,4'-methylenediphenyl diisocyanate (101-68-8)	Worker	dermal	short term (systemic effects)	28,7 mg/cm ²	
'4,4'-methylenediphenyl diisocyanate (101-68-8)	Worker	inhalation	short term (local effects)	0,1 mg/m ³	
'4,4'-methylenediphenyl diisocyanate (101-68-8)	Worker	inhalation	long term (systemic effects)	0,05 mg/m ³	
'4,4'-methylenediphenyl diisocyanate (101-68-8)	Worker	inhalation	long term (local effects)	0,05 mg/m ³	
'4,4'-methylenediphenyl diisocyanate (101-68-8)	Consumer	dermal	short term (systemic effects)	25 mg/kg bw/day	
'4,4'-methylenediphenyl diisocyanate (101-68-8)	Consumer	inhalation	short term (systemic effects)	0,05 mg/m ³	
'4,4'-methylenediphenyl diisocyanate (101-68-8)	Consumer	oral	short term (systemic effects)	20 mg/kg bw/day	
'4,4'-methylenediphenyl diisocyanate (101-68-8)	Consumer	dermal	short term (local effects)	17,2 mg/cm ²	
'4,4'-methylenediphenyl diisocyanate (101-68-8)	Consumer	inhalation	short term (local effects)	0,05 mg/m ³	
'4,4'-methylenediphenyl diisocyanate (101-68-8)	Consumer	inhalation	long term (systemic effects)	0,025 mg/m ³	
'4,4'-methylenediphenyl diisocyanate (101-68-8)	Consumer	inhalation	long term (local effects)	0,025 mg/m ³	

8.1.4. PNEC values

For components

Name	Exposure route	Value	Remark
'4,4'-methylenediphenyl diisocyanate (101-68-8)	fresh water	1 mg/L	
'4,4'-methylenediphenyl diisocyanate (101-68-8)	marine water	0,1 mg/L	
'4,4'-methylenediphenyl diisocyanate (101-68-8)	soil	1 mg/kg	
'4,4'-methylenediphenyl diisocyanate (101-68-8)	water treatment plant	1 mg/L	

SAFETY DATA SHEET

8.2. EXPOSURE CONTROLS

8.2.1. Appropriate engineering control

Substance/mixture related measures to prevent exposure during identified uses

In the case of allergies, asthma, recurrent or chronic breathing difficulty avoid contact with products of this type. Persons who process this product should regularly undergo lung function tests. Use good personal hygiene practices – wash hands at breaks and when done working with material. Avoid contact with eyes and skin. Do not breathe vapours/aerosols. Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke while working.

Organisational measures to prevent exposure

Remove all contaminated clothes immediately and wash them before reuse. Keep eyewash bottles or personal eyewash units and emergency showers available.

Technical measures to prevent exposure

Provide good ventilation and local exhaust in areas with increased concentration.

8.2.2. Personal protective equipment

Eye and face protection

Safety glasses with side protection (EN 166).

Hand protection

Protective gloves (EN 374). Observe the manufacturer's instructions regarding the use, storage, maintenance and replacement of gloves. In case of damage or at the first signs of wear and tear, change the gloves immediately. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. In case of prolonged exposure, wear protective gloves of at least Class 5 (penetration time above 240 minutes). In case of short exposure, wear protective gloves of at least Class 3 (penetration time 60 minutes).

Appropriate materials

Material	Thickness	Penetration Time	Remark
Butyl rubber			
PE			
Neoprene			
Nitrile			
PVC			
Viton (fluorinated rubber)			
chloroprene rubber			
Ethyl vinyl alcohol copolymers laminated ("EVAL")			

Skin protection

Cotton protective clothing and shoes that cover the entire foot (EN ISO 20345).

Respiratory protection

Not needed under normal use and adequate ventilation. At elevated concentrations of vapours/aerosols in the air wear a mask (EN 140) with filter A2-P2 (EN 14387).

Thermal hazards

-

8.2.3. Environmental exposure controls

Instruction measures to prevent exposure

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

Technical measures to prevent exposure

In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SAFETY DATA SHEET

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

- Physical state:	liquid
- Colour:	
- Odour:	

Important health, safety and environmental information

- pH	No information.
- Melting point/freezing point	No information.
- Initial boiling point/boiling range	245 °C
- Flash point	230 °C (Closed cup)
- Evaporation rate	No information.
- Flammability (solid, gas)	No information.
- Explosion limits (vol%)	No information.
- Vapour pressure	No information.
- Vapour density	No information.
- Density	Density: 1,20 – 1,30 g/cm ³ at 23 °C (IKM 4/24)
- Solubility	No information.
- Partition coefficient	No information.
- Auto-ignition temperature	No information.
- Decomposition temperature	No information.
- Viscosity	No information.
- Explosive properties	No information.
- Oxidising properties	No information.

9.2. OTHER INFORMATION

- Remarks:	
------------	--

SECTION 10. STABILITY AND REACTIVITY

10.1. REACTIVITY

Reacts with water: may cause overpressure in closed vessel (CO₂).

10.2. CHEMICAL STABILITY

Product is stable under normal conditions of use, recommended handling and storage conditions.

10.3. POSSIBILITY OF HAZARDOUS REACTIONS

Product reacts slowly with water, releasing CO₂, which can cause overpressure in closed containers. Danger of explosion.. Exothermic reaction with materials containing active hydrogen groups. The reaction becomes progressively more vigorous and can be violent at higher temperatures if the miscibility of the reaction partners is good or is supported by stirring or by the presence of solvents. MDI is not soluble in water and is heavier than water. It reacts with water, creating polyurea and CO₂.

10.4. CONDITIONS TO AVOID

-

10.5. INCOMPATIBLE MATERIALS

Water, alcohols, amines, bases, and acids.

SAFETY DATA SHEET

10.6. HAZARDOUS DECOMPOSITION PRODUCTS

Under normal use conditions no hazardous decomposition products are expected. In case of fire/explosion vapours/gases that pose a health hazard are released. Carbon dioxide; Carbon monoxide.

Nitrogen oxides.

Hydrocarbons. HCN.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. INFORMATION ON TOXICOLOGICAL EFFECTS

(a) Acute toxicity

Name	Exposure route	Type	Species	Time	Value	Method	Remark
For product	inhalation (aerosol)	LC ₅₀	rat	4 h	ca. 490 mg/m ³		
polymeric MDI (9016-87-9)	inhalation	LC ₅₀	rat (male/female)	4 h	310 mg/l		dust/aerosol
polymeric MDI (9016-87-9)	dermal	LD ₅₀	rabbit (male/female)		> 9400 mg/kg		
polymeric MDI (9016-87-9)	oral	LD ₅₀	rat (male)		> 10000 mg/kg		
'4,4'-methylenediphenyl diisocyanate (101-68-8)	oral	LD ₅₀	rat (male)		> 10000 mg/kg		
'4,4'-methylenediphenyl diisocyanate (101-68-8)	dermal	LD ₅₀	rabbit (male/female)		> 9400 mg/kg		
'4,4'-methylenediphenyl diisocyanate (101-68-8)	inhalation	LC ₅₀	rat (male/female)	4 h	0,49 mg/l		dust/aerosol

Additional information: Harmful if inhaled.

(b) Skin corrosion/irritation

Name	Species	Time	Result	Method	Remark
polymeric MDI (9016-87-9)	rabbit		Mild irritating.	OECD 404	
'4,4'-methylenediphenyl diisocyanate (101-68-8)	rabbit		Irritating.	OECD 404	

Additional information: Irritating to respiratory system, eyes and skin.

(c) Serious eye damage/irritation

Name	Species	Time	Result	Method	Remark
polymeric MDI (9016-87-9)	rabbit		Non-irritant.	OECD 405, GLP	
polymeric MDI (9016-87-9)					According to the OECD Guideline 405 it is not irritating, but according to data on occupational exposures of humans, the substance is regarded as irritating to eyes.
'4,4'-methylenediphenyl diisocyanate (101-68-8)	rabbit		Non-irritant.	OECD 405, GLP	
'4,4'-methylenediphenyl diisocyanate (101-68-8)					According to the OECD Guideline 405 it is not irritating, but according to data on occupational exposures of humans, the substance is regarded as irritating to eyes.

SAFETY DATA SHEET

(d) Respiratory or skin sensitisation

Name	Exposure route	Species	Time	Result	Method	Remark
polymeric MDI (9016-87-9)	dermal	mouse		Sensitizing.		
polymeric MDI (9016-87-9)	inhalation	guinea pig		Sensitizing.		
'4,4'-methylenediphenyl diisocyanate (101-68-8)	dermal	mouse		Sensitizing.		
'4,4'-methylenediphenyl diisocyanate (101-68-8)	inhalation	guinea pig		Sensitizing.		

Additional information: If the person became sensitized in the past, he/she can have a severe allergic reaction upon contact with the substance, even though he/she is exposed to very low levels. May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

(e) (Germ cell) mutagenicity

Name	Type	Species	Time	Result	Method	Remark
polymeric MDI (9016-87-9)	in-vivo mutagenicity			Negative.	OECD 474	
'4,4'-methylenediphenyl diisocyanate (101-68-8)		Bacteria		Negative.	EU EC B.13/14 Mutagenicity - Reverse Mutation Test using Bacteria	
'4,4'-methylenediphenyl diisocyanate (101-68-8)				Negative.	474 Mammalian Erythrocyte Micronucleus Test	

(f) Carcinogenicity

Name	Exposure route	Type	Species	Time	Value	Result	Method	Remark
polymeric MDI (9016-87-9)	inhalation		rat	2 years		negative	OECD 453 Combined Chronic Toxicity/Carcinogenicity Studies	5 days per week
polymeric MDI (9016-87-9)	inhalation		rat	2 years		negative	EU	5 days per week
'4,4'-methylenediphenyl diisocyanate (101-68-8)	inhalation		Rat (lungs)	2 years		Positive	OECD 453 Combined Chronic Toxicity/Carcinogenicity Studies	5 days per week

(g) Reproductive toxicity

Name	Reproductive toxicity type	Type	Species	Time	Value	Result	Method	Remark
polymeric MDI (9016-87-9)	Teratogenicity		rat (male/female)		4 mg/m ³		OECD 414	
'4,4'-methylenediphenyl diisocyanate (101-68-8)	Teratogenicity		rat (male/female)		12 mg/m ³		OECD 414	

Summary of evaluation of the CMR properties

Suspected of causing cancer. Rats have been exposed for two years to a respirable aerosol of polymeric MDI which resulted in chronic pulmonary irritation at high concentrations. Only at the top level (6 mg/m³), there was a significant incidence of a benign tumour of the lung (adenoma) and one malignant tumour (adenocarcinoma). There were no lung tumours at 1 mg/m³ and no effects at 0.2 mg/m³. The total incidence of tumors, benign and malignant and the number of animals with tumor was no different than in the control group. The increased incidence of lung tumours is associated with prolonged respiratory irritation and the concurrent accumulation of yellow material in the lung, which occurred throughout the study. In the absence of prolonged exposure to high concentrations leading to chronic irritation and lung damage, it is highly unlikely that tumour formation will occur. No birth defects were seen in two independent animal (rat) studies. Fetotoxicity was observed at doses that were extremely toxic (including lethal) to the mother. Fetotoxicity was not observed at doses that were not maternally toxic. The doses used in these studies were maximal, respirable concentrations, which are well in excess of defined occupational exposure limits.

SAFETY DATA SHEET

(h) STOT-single exposure

Name	Exposure route	Type	Species	Time	Organ	Value	Result	Method	Remark
polymeric MDI (9016-87-9)	inhalation	-			Respiratory tract		Category 3		Respiratory tract irritation
'4,4'-methylenediphenyl diisocyanate (101-68-8)	inhalation	-			Respiratory tract		Category 3		Respiratory tract irritation

(i) STOT-repeated exposure

Name	Exposure route	Type	Species	Time	Organ	Value	Result	Method	Remark
polymeric MDI (9016-87-9)	inhalation	-			Respiratory tract		Category 2		
polymeric MDI (9016-87-9)	inhalation	NOEC				0,2 mg/m ³		OECD 453 Combined Chronic Toxicity/Carcinogenicity Studies	Dust and mist.
'4,4'-methylenediphenyl diisocyanate (101-68-8)	inhalation	-			Respiratory tract		Category 2		

Additional information: May cause damage to organs through prolonged or repeated exposure if inhaled.

(j) Aspiration hazard

No information.

SECTION 12. ECOLOGICAL INFORMATION

12.1. TOXICITY

12.1.1. Acute (short-term) toxicity

For components

Substance (CAS Nr.)	Type	Value	Exposure time	Species	Organism	Method	Remark
polymeric MDI (9016-87-9)	EC ₅₀	> 100 mg/kg	3 h	bacteria		OECD 209	static system
	EC ₅₀	> 1000 mg/L	24 h	crustacea	<i>Daphnia magna</i>	OECD 202	static system
	LC ₅₀	> 1000 mg/L	96 h	fish		OECD 203	static system
	EC ₅₀	> 1640 mg/L	72 h	algae		OECD 201	static system
'4,4'-methylenediphenyl diisocyanate (101-68-8)	LC ₅₀	> 1000 mg/L	96 h	fish		OECD 203	static system
	EC ₅₀	> 1000 mg/L	24 h	daphnia	<i>Daphnia sp.</i>	OECD 202	static system

SAFETY DATA SHEET

12.1.2. Chronic (long-term) toxicity

For components

Substance (CAS Nr.)	Type	Value	Exposure time	Species	Organism	Method	Remark
polymeric MDI (9016-87-9)	NOEC	> 10 mg/l	21 days	crustacea	<i>Daphnia magna</i>	OECD 211	semi-static system
	NOEC	> 10000 mg/l	112 days	<i>Daphnia</i>			static system
	NOEC	> 10000 mg/kg	112 days	fish			static system
	NOECr	> 10000 mg/l	112 days	algae			static system
'4,4'-methylenediphenyl diisocyanate (101-68-8)	NOEC	> 10 mg/l	21 days	Magna Daphnia	<i>Daphnia magna</i>	OECD 211	semi-static system

12.2. PERSISTENCE AND DEGRADABILITY

12.2.1. Abiotic degradation, physical- and photo-chemical elimination

For product

Environment	Type / Method	Half Time	Evaluation	Method	Remark
Air	photodegradation				OH radical degradation

For components

Substance (CAS Nr.)	Environment	Type / Method	Half Time	Evaluation	Method	Remark
polymeric MDI (9016-87-9)	water	hydrolysis	0,8 days	poor	half-life	
'4,4'-methylenediphenyl diisocyanate (101-68-8)	water	hydrolysis	0,83 days	poor	half-life	

12.2.2. Biodegradation

For components

Substance (CAS Nr.)	Type	Rate	Time	Evaluation	Method	Remark
polymeric MDI (9016-87-9)	aerobic		28 days	0 %	OECD 302C Test	
'4,4'-methylenediphenyl diisocyanate (101-68-8)	aerobic		28 days	0 %	OECD 302C Test	

12.3. BIOACCUMULATIVE POTENTIAL

12.3.1. Partition coefficient

For components

Substance (CAS Nr.)	Media	Value	Temperature	pH	Concentration	Method
'4,4'-methylenediphenyl diisocyanate (101-68-8)	Octanol-water (log Pow)	4,51				

12.3.2. Bioconcentration factor (BCF)

For components

Substance (CAS Nr.)	species	Organism	Value	Duration	Evaluation	Method	Remark
polymeric MDI (9016-87-9)	BCF		200		high		
'4,4'-methylenediphenyl diisocyanate (101-68-8)	BCF		200		high		

12.4. MOBILITY IN SOIL

12.4.1. Known or predicted distribution to environmental compartments

No information.

SAFETY DATA SHEET

12.4.2. Surface tension

No information.

12.4.3. Adsorption/Desorption

No information.

12.5. RESULTS OF PBT AND VPVB ASSESSMENT

No evaluation.

12.6. OTHER ADVERSE EFFECTS

No information.

12.7. ADDITIONAL INFORMATION

For product

Do not allow to reach ground water, water courses or sewage system.

Depending on the production and use of the substance, it is unlikely that it may lead to increased concentrations in the air or water.

Immiscible with water, but will react with water to produce inert and non-biodegradable solids.

Conversion to soluble products, including diamino- diphenylmethane (MDA), is very low under the optimal laboratory conditions of good dispersion and low concentration.

Isocyanates react with water to form an insoluble polyurea.

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. WASTE TREATMENT METHODS

13.1.1. Product / Packaging disposal

Waste chemical

The generation of waste should be avoided or minimised wherever possible. Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste. Do not allow product to reach drains/sewage systems.

Waste codes / waste designations according to LoW

08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances

16 03 05* - organic wastes containing dangerous substances

Packaging

Deliver completely emptied containers to approved waste disposal authorities. Empty containers or liners may contain product residues. Uncleaned containers are classified as hazardous waste - they should be handled in the same manner as the contents.

13.1.2. Waste treatment-relevant information

-

13.1.3. Sewage disposal-relevant information

-

13.1.4. Other disposal recommendations

-

SECTION 14. TRANSPORT INFORMATION

14.1. UN NUMBER

Not applicable.

14.2. UN PROPER SHIPPING NAME

ADR, RID, IMDG, ADN, IATA: Not dangerous according to transport regulations.

SAFETY DATA SHEET

14.3. TRANSPORT HAZARD CLASS(ES)

Not applicable.

14.4. PACKING GROUP

Not applicable.

14.5. ENVIRONMENTAL HAZARDS

NO.

14.6. SPECIAL PRECAUTIONS FOR USER

Not applicable.

14.7. TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL AND THE IBC CODE

Not applicable.

SECTION 15. REGULATORY INFORMATION

15.1. SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE

- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (including last amendment Commission Regulation (EU) 2015/830)

- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

15.1.1. Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-guideline)

Not applicable.

15.1.2. Special instructions

Regulation (EC) No. 1907/2006 (REACH) Annex XVII - Terms of restriction: 56 Methylene-diphenyl diisocyanate (MDI):

1. Shall not be placed on the market after 27 December 2010, as a constituent of mixtures in concentrations equal to or greater than 0,1 % by weight of MDI for supply to the general public, unless suppliers shall ensure before the placing on the market that the packaging:

(a) contains protective gloves which comply with the requirements of Council Directive 89/686/ EEC;

(b) is marked visibly, legibly and indelibly as follows, and without prejudice to other Community legislation concerning the classification, packaging and labelling of substances and mixtures:

„— Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

— Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

— This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.“

2. By way of derogation, paragraph 1(a) shall not apply to hot melt adhesives.

Regulation (EC) No. 1907/2006 (REACH) Annex XVII - Terms of restriction: 74.

15.2. CHEMICAL SAFETY ASSESSMENT

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16. OTHER INFORMATION

Indication of changes

-

Abbreviations and acronyms

ATE - Acute Toxicity Estimate

ADR - Agreement concerning the International Carriage of Dangerous Goods by Road

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

CEN - European Committee for Standardisation

C&L - Classification and Labelling

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

SAFETY DATA SHEET

CAS# - Chemical Abstracts Service number
CMR - Carcinogen, Mutagen, or Reproductive Toxicant
CSA - Chemical Safety Assessment
CSR - Chemical Safety Report
DMEL - Derived Minimal Effect Level
DNEL - Derived No Effect Level
DPD - Dangerous Preparations Directive 1999/45/EC
DSD - Dangerous Substances Directive 67/548/EEC
DU - Downstream User
EC - European Community
ECHA - European Chemicals Agency
EC-Number - EINECS and ELINCS Number (see also EINECS and ELINCS)
EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway)
EEC - European Economic Community
EINECS - European Inventory of Existing Commercial Substances
ELINCS - European List of notified Chemical Substances
EN - European Standard
EQS - Environmental Quality Standard
EU - European Union
Euphrac - European Phrase Catalogue
EWC - European Waste Catalogue (replaced by LoW – see below)
GES - Generic Exposure Scenario
GHS - Globally Harmonized System
IATA - International Air Transport Association
ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG - International Maritime Dangerous Goods
IMSBC - International Maritime Solid Bulk Cargoes
IT - Information Technology
IUCLID - International Uniform Chemical Information Database
IUPAC - International Union for Pure Applied Chemistry
JRC - Joint Research Centre
Kow - octanol-water partition coefficient
LC₅₀ - Lethal Concentration to 50 % of a test population
LD₅₀ - Lethal Dose to 50% of a test population (Median Lethal Dose)
LE - Legal Entity
LoW - List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)
LR - Lead Registrant
M/I - Manufacturer / Importer
MS - Member States
MSDS - Material Safety Data Sheet
OC - Operational Conditions
OECD - Organization for Economic Co-operation and Development
OEL - Occupational Exposure Limit
OJ - Official Journal
OR - Only Representative
OSHA - European Agency for Safety and Health at work
PBT - Persistent, Bioaccumulative and Toxic substance
PEC - Predicted Effect Concentration
PNEC(s) - Predicted No Effect Concentration(s)
PPE - Personal Protection Equipment
(Q)SAR - Qualitative Structure Activity Relationship
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
RIP - REACH Implementation Project
RMM - Risk Management Measure
SCBA - Self-Contained Breathing Apparatus
SDS - Safety data sheet
SIEF - Substance Information Exchange Forum
SME - Small and Medium sized Enterprises
STOT - Specific Target Organ Toxicity
(STOT) RE - Repeated Exposure
(STOT) SE - Single Exposure
SVHC - Substances of Very High Concern

SAFETY DATA SHEET

UN - United Nations
vPvB - Very Persistent and Very Bioaccumulative

Key literature references and sources for data

-

List of relevant H phrases

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer .
- H373 May cause damage to organs through prolonged or repeated exposure .

The information of this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under Section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.