

## SAFETY DATA SHEET

### SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. PRODUCT IDENTIFIER

Product name

**PARKETOLIT 1555B**



chemius.net/Hqlc5

#### 1.2. RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST

Relevant identified uses

Adhesive for wood flooring - component B

Uses advised against

No information.

#### 1.3. DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Supplier

MITOL, tovarna lepil, d.o.o., Sežana  
Address: Partizanska c. 78 Sežana, Slovenia  
Phone: +386 5 73 12 300  
Fax: +386 5 73 12 390  
E-mail: lilijana.kocjan@mitol.si  
Point of contact for safety info: Lilijana Kocjan Žorž

#### 1.4. EMERGENCY TELEPHONE NUMBER

112

+386 5 73 12 300 (8:00-16:00)

### SECTION 2. HAZARDS IDENTIFICATION

#### 2.1 CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

Classification according to Regulation (EC) No 1272/2008 (CLP)

Acute Tox. 4; H302 Harmful if swallowed.  
Skin Corr. 1B; H314 Causes severe skin burns and eye damage.  
Skin Sens. 1A; H317 May cause an allergic skin reaction.  
Eye Dam. 1; H318 Causes serious eye damage.  
Acute Tox. 4; H332 Harmful if inhaled.  
STOT RE 2; H373 May cause damage to organs through prolonged or repeated exposure.  
Aquatic Chronic 3; H412 Harmful to aquatic life with long lasting effects.

## SAFETY DATA SHEET

### 2.2 LABEL ELEMENTS

#### 2.2.1. Labelling according to Regulation (EC) No 1272/2008 [CLP]



Signal word: **Danger**

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

P102 Keep out of reach of children.

P260 Do not breathe mist/vapours.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with national regulation.

#### 2.2.2. Contains:

benzyl alcohol (CAS: 100-51-6, EC: 202-859-9, Index: 603-057-00-5)

3-aminomethyl-3,5,5-trimethylcyclohexylamine (CAS: 2855-13-2, EC: 220-666-8, Index: 612-067-00-9)

4,4'-isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine (CAS: 38294-64-3, EC: 500-101-4)

4,4'-methylenebis(cyclohexylamine) (CAS: 1761-71-3, EC: 217-168-8)

2,4,6-tris(dimethylaminomethyl)phenol (CAS: 90-72-2, EC: 202-013-9, Index: 603-069-00-0)

methyleneoxide, polymer with benzenamine, hydrogenated (CAS: 135108-88-2, EC: 603-894-6)

#### 2.2.3. Special provisions

Special hazards are not known or expected.

### 2.3. OTHER HAZARDS

No information.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. SUBSTANCES

For mixtures see 3.2.

## SAFETY DATA SHEET

### 3.2. MIXTURES

Name	CAS EC Index	%	Classification according to Regulation (EC) No 1272/2008 (CLP)	Specific Conc. Limits	REACH Registration No.
benzyl alcohol	100-51-6 202-859-9 603-057-00-5	20-50	Acute Tox. 4; H302 Eye Irrit. 2; H319 Acute Tox. 4; H332		01-2119492630-38
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2 220-666-8 612-067-00-9	0-45	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1B; H314 Skin Sens. 1A; H317 Eye Dam. 1; H318 Aquatic Chronic 3; H412		01-2119514687-32
4,4'-isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine	38294-64-3 500-101-4 -	5-25	Skin Corr. 1B; H314 Skin Sens. 1; H317 Eye Dam. 1; H318 Aquatic Chronic 3; H412		01-2119965165-33
4,4'-methylenebis(cyclohexylamine)	1761-71-3 217-168-8 -	2,5-15	Acute Tox. 4; H302 Skin Corr. 1B; H314 Skin Sens. 1; H317 Eye Dam. 1; H318 STOT RE 2; H373		01-2119541673-38
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2 202-013-9 603-069-00-0	5-10	Skin Corr. 1C; H314 Eye Dam. 1; H318		01-2119560597-27
methyleneoxide, polymer with benzenamine, hydrogenated	135108-88-2 603-894-6 -	1-5	Acute Tox. 4; H302 Skin Corr. 1C; H314 Skin Sens. 1; H317 STOT RE 2; H373 Aquatic Chronic 3; H412		01-2119983522-33

## SAFETY DATA SHEET

---

### SECTION 4. FIRST AID MEASURES

---

#### 4.1. DESCRIPTION OF FIRST AID MEASURES

##### General notes

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Never give anything by mouth to an unconscious person. Place patient in recovery position and ensure airway patency.

##### Following inhalation

Remove patient to fresh air - move out of dangerous area. If victim is not breathing give artificial respiration. Seek medical help immediately.

##### Following skin contact

Immediately remove contaminated clothing. Wash affected skin areas thoroughly with plenty of water and soap. Immediately obtain professional medical help!

##### Following eye contact

Immediately flush eyes with running water, keeping eyelids apart. After 5 minutes of rinsing, remove contact lenses, if present, and continue rinsing. Consult a physician immediately!

##### Following ingestion

Do not induce vomiting! Rinse mouth with water and drink a glass of water by sips! Immediately consult a doctor. Show the physician the safety data sheet or label.

#### 4.2. MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

##### Inhalation

Corrosive.  
Harmful.  
Negative effects can affect liver, kidney, and central nervous system.  
Excessive exposure to spray mist, fog, or vapours may cause respiratory irritation.  
Coughing, sneezing, nasal discharge, labored breathing.

##### Skin contact

Redness, ulcers, pain.  
May cause sensitisation by skin contact (symptoms: itching, redness, rashes).

##### Eye contact

Contact with eyes can cause severe injuries.  
Discomfort or pain, excessive blinking, lacrimation and redness, swelling of the conjunctiva.

##### Ingestion

Harmful to health.  
May cause nausea/vomiting and diarrhea.  
May cause abdominal discomfort.  
Causes corrosions in mouth, throat, digestive tract.

#### 4.3. INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

-

### SECTION 5. FIREFIGHTING MEASURES

---

#### 5.1. EXTINGUISHING MEDIA

##### Suitable extinguishing media

Carbon dioxide. Dry chemical powder. Water spray. Alcohol resistant foam.

##### Unsuitable extinguishing media

Full water jet.

## SAFETY DATA SHEET

---

### 5.2. SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

#### Hazardous combustion products

In case of heating harmful vapours/gases can be generated. In the event of fire the following can be generated: carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>). In the event of fire the following is released: nitrogen oxides (NOx).

### 5.3. ADVICE FOR FIREFIGHTERS

#### Protective actions

In case of fire do not breathe fumes/gases. Cool containers at risk with water spray. If possible remove containers from endangered area.

#### Special protective equipment for firefighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (EN 137).

#### Additional information

Contaminated firefighting water must be disposed of in accordance with the regulations; do not allow to reach the sewage system. Contaminated firefighting water and fire residues must be disposed of in accordance with the local regulations.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

---

### 6.1. PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

#### 6.1.1. For non-emergency personnel

##### **Protective equipment**

Use personal protective equipment (Section 8).

##### **Emergency procedures**

Ensure adequate ventilation. Prevent access to unprotected personnel. Prevent access to unauthorised personnel. Do not use open fire and keep away all sources of ignition. No action shall be taken involving any personal risk or without suitable training. Do not breathe vapour or mist. Avoid contact with skin and eyes. Avoid contact with spilled product or contaminated surfaces.

#### 6.1.2. For emergency responders

Use personal protective equipment.

### 6.2. ENVIRONMENTAL PRECAUTIONS

Do not allow product to reach water/drains/sewage systems or permeable soil. If accidental large entry into water or ground occurs, inform responsible authorities.

### 6.3. METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

#### 6.3.1. For containment

Stem the spill if this does not pose risks.

#### 6.3.2. For cleaning up

Absorb product (with inert material), collect it in special container and dispose it to a licensed hazardous-waste disposal contractor. Dispose in accordance with applicable regulations (see Section 13).

#### 6.3.3. Other information

-

### 6.4. REFERENCE TO OTHER SECTIONS

See also Sections 8 and 13.

## SAFETY DATA SHEET

---

### SECTION 7. HANDLING AND STORAGE

---

#### 7.1. PRECAUTIONS FOR SAFE HANDLING

##### 7.1.1. Protective measures

###### **Measures to prevent fire**

Ensure adequate ventilation. Keep away from sources of ignition - no smoking. Take precautionary measures against static discharges.

###### **Measures to prevent aerosol and dust generation**

-

###### **Measures to protect the environment**

-

##### 7.1.2. Advice on general occupational hygiene

Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Avoid contact with skin, eyes and clothes. Do not breathe vapours/mist. Remove contaminated clothes and wash them before reuse. Refer to instructions on label and regulations for safety and health at work. Consider measures required in Section 8 of this safety data sheet.

#### 7.2. CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

##### 7.2.1. Technical measures and storage conditions

Store in accordance with local regulations. Keep in cool and well ventilated area. Keep away from food, drink and animal feeding stuffs. Keep away from oxidizers, strong alkalies and acids. Storage temperature +5°C to 35°C.

##### 7.2.2. Packaging materials

-

##### 7.2.3. Requirements for storage rooms and vessels

Close opened containers after use. Put the containers upright to prevent from leaking.

##### 7.2.4. Storage class

-

##### 7.2.5. Further information on storage conditions

-

#### 7.3. SPECIFIC END USE(S)

##### **Recommendations**

-

##### **Industrial sector specific solutions**

-

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

#### 8.1. CONTROL PARAMETERS

##### 8.1.1. Occupational exposure limit values

No information.

##### 8.1.2. Information on monitoring procedures

BS EN 14042:2003 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 482:2012+A1:2015 Workplace exposure. General requirements for the performance of procedures for the measurement of chemical agents. BS EN 689:2018 Workplace exposure. Measurement of exposure by inhalation to chemical agents. Strategy for testing compliance with occupational exposure limit values.

## SAFETY DATA SHEET

### 8.1.3. DNEL/DMEL values

#### For components

Name	Type	Exposure route	Exposure frequency	Value	Remark
benzyl alcohol (100-51-6)	Worker	inhalation	long term (systemic effects)	22 mg/m <sup>3</sup>	
benzyl alcohol (100-51-6)	Worker	dermal	long term (systemic effects)	8 mg/kg bw/day	
benzyl alcohol (100-51-6)	Worker	inhalation	short term (systemic effects)	110 mg/m <sup>3</sup>	
benzyl alcohol (100-51-6)	Consumer	inhalation	long term (systemic effects)	5,4 mg/m <sup>3</sup>	
benzyl alcohol (100-51-6)	Consumer	inhalation	short term (systemic effects)	27 mg/m <sup>3</sup>	
benzyl alcohol (100-51-6)	Consumer	dermal	long term (systemic effects)	4 mg/kg bw/day	
benzyl alcohol (100-51-6)	Consumer	dermal	short term (systemic effects)	20 mg/kg bw/day	
benzyl alcohol (100-51-6)	Worker	dermal	short term (systemic effects)	40 mg/kg bw/day	
benzyl alcohol (100-51-6)	Consumer	oral	long term (systemic effects)	4 mg/kg bw/day	
benzyl alcohol (100-51-6)	Consumer	oral	short term (systemic effects)	20 mg/kg bw/day	
3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)	Worker	inhalation	long term (local effects)	0,073 mg/m <sup>3</sup>	
3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)	Worker	inhalation	short term (local effects)	0,073 mg/m <sup>3</sup>	
3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)	Consumer	oral	long term (systemic effects)	0,526 mg/kg bw/day	

## SAFETY DATA SHEET

### 8.1.4. PNEC values

#### For components

Name	Exposure route	Value	Remark
benzyl alcohol (100-51-6)	fresh water	1 mg/L	
benzyl alcohol (100-51-6)	water, intermittent release	2,3 mg/L	
benzyl alcohol (100-51-6)	marine water	0,1 mg/L	
benzyl alcohol (100-51-6)	water treatment plant	39 mg/L	
benzyl alcohol (100-51-6)	fresh water sediment	5,27 mg/kg	dry weight
benzyl alcohol (100-51-6)	marine water sediment	0,527 mg/kg	dry weight
benzyl alcohol (100-51-6)	soil	0,456 mg/kg	dry weight
3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)	fresh water	0,06 mg/L	
3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)	marine water	0,006 mg/L	
3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)	water, intermittent release	0,23 mg/L	
3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)	water treatment plant	3,18 mg/L	
3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)	fresh water sediment	5,784 mg/kg	dry weight
3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)	marine water sediment	0,578 mg/kg	dry weight
3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)	soil	1,121 mg/kg	dry weight
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	fresh water	0,084 mg/L	
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	water, intermittent release	0,84 mg/L	fresh water
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	marine water	0,008 mg/L	
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	water treatment plant	0,2 mg/L	

## 8.2. EXPOSURE CONTROLS

### 8.2.1. Appropriate engineering control

#### Substance/mixture related measures to prevent exposure during identified uses

Handle in accordance with good industrial hygiene and safety practice. Use good personal hygiene practices – wash hands at breaks and when done working with material. Avoid contact with eyes and skin. Do not breathe vapours/aerosols. Do not eat, drink or smoke while working.

#### Technical measures to prevent exposure

Provide good ventilation and local exhaust in areas with increased concentration.

### 8.2.2. Personal protective equipment

#### Eye and face protection

Tight fitting protective goggles (EN 166).

#### Hand protection

Protective gloves (EN 374). Observe the manufacturer's instructions regarding the use, storage, maintenance and replacement of gloves. In case of damage or at the first signs of wear and tear, change the gloves immediately.

#### Skin protection

Cotton protective clothing and shoes that cover the entire foot (EN ISO 20345).

#### Respiratory protection

Wear suitable protective breathing mask (EN 136) with filter A2-P2 (EN 14387).

#### Thermal hazards

-

### 8.2.3. Environmental exposure controls

#### Technical measures to prevent exposure

Do not allow product to reach drains, sewage systems or ground water.



## SAFETY DATA SHEET

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1. INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

- Physical state:	liquid
- Colour:	light yellow
- Odour:	amine like

#### Important health, safety and environmental information

- pH	No information.
- Melting point/freezing point	No information.
- Initial boiling point/boiling range	No information.
- Flash point	No information.
- Evaporation rate	No information.
- Flammability (solid, gas)	No information.
- Explosion limits (vol%)	No information.
- Vapour pressure	No information.
- Vapour density	No information.
- Density	No information.
- Solubility	No information.
- Partition coefficient	No information.
- Auto-ignition temperature	No information.
- Decomposition temperature	No information.
- Viscosity	No information.
- Explosive properties	No information.
- Oxidising properties	No information.

#### 9.2. OTHER INFORMATION

- Remarks:	
------------	--

### SECTION 10. STABILITY AND REACTIVITY

#### 10.1. REACTIVITY

-

#### 10.2. CHEMICAL STABILITY

Product is stable under normal conditions of use, recommended handling and storage conditions.

#### 10.3. POSSIBILITY OF HAZARDOUS REACTIONS

-

#### 10.4. CONDITIONS TO AVOID

No special precautions required. Consider the directions for use and storage. Does not decompose if used and stored as instructed. Avoid heating.

#### 10.5. INCOMPATIBLE MATERIALS

Strong oxidising agents.

Strong acids.

Strong bases.

## SAFETY DATA SHEET

### 10.6. HAZARDOUS DECOMPOSITION PRODUCTS

Under normal use conditions no hazardous decomposition products are expected. In case of fire/explosion vapours/gases that pose a health hazard are released. Carbon dioxide; Carbon monoxide.  
Nitrogen oxides.

## SECTION 11. TOXICOLOGICAL INFORMATION

### 11.1. INFORMATION ON TOXICOLOGICAL EFFECTS

#### (a) Acute toxicity

Name	Exposure route	Type	Species	Time	Value	Method	Remark
benzyl alcohol (100-51-6)	oral	LD <sub>50</sub>	rat (male)		1620 mg/kg		ECHA
benzyl alcohol (100-51-6)	inhalation (aerosol)	LC <sub>50</sub>	rat	4 h	> 4178 mg/m <sup>3</sup>	OECD 403	
3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)	oral	LD <sub>50</sub>	rat		1030 mg/kg	OECD 401	
3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)	dermal	LD <sub>50</sub>	rat		> 2000 mg/kg	OECD 402	
3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)	inhalation	LC <sub>50</sub>	rat	4 h	> 5,01 mg/l	OECD 403	
4,4'-methylenebis(cyclohexylamine) (1761-71-3)	oral	LD <sub>50</sub>	rat		625 mg/kg		
4,4'-methylenebis(cyclohexylamine) (1761-71-3)	dermal	LD <sub>50</sub>	rabbit		2110 mg/kg		
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	oral	LD <sub>50</sub>	rat		2169 mg/kg		
methyleneoxide, polymer with benzenamine, hydrogenated (135108-88-2)	oral	LD <sub>50</sub>	rat		367 mg/kg		
methyleneoxide, polymer with benzenamine, hydrogenated (135108-88-2)	dermal	LD <sub>50</sub>	rabbit		> 2000 mg/kg		

**Additional information:** Harmful if swallowed. Harmful if inhaled.

#### (b) Skin corrosion/irritation

Name	Species	Time	Result	Method	Remark
benzyl alcohol (100-51-6)	rabbit		Irritating.	OECD 404	
3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)	rabbit		Corrosive	OECD 404	

**Additional information:** Corrosive.

#### (c) Serious eye damage/irritation

Name	Species	Time	Result	Method	Remark
benzyl alcohol (100-51-6)	rabbit		Mild irritating.	OECD 405	
3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)	rabbit		Corrosive.	OECD 405	

**Additional information:** Causes serious eye damage.

#### (d) Respiratory or skin sensitisation

Name	Exposure route	Species	Time	Result	Method	Remark
benzyl alcohol (100-51-6)	dermal	guinea pig		Negative.	OECD 406	
3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)	dermal	guinea pig		Sensitizing.	OECD 406	

**Additional information:** May cause an allergic skin reaction.

## SAFETY DATA SHEET

---

(e) (Germ cell) mutagenicity

No information.

(f) Carcinogenicity

No information.

(g) Reproductive toxicity

No information.

Summary of evaluation of the CMR properties

No information.

(h) STOT-single exposure

No information.

(i) STOT-repeated exposure

**Additional information:** May cause damage to organs through prolonged or repeated exposure.

(j) Aspiration hazard

No information.

## SAFETY DATA SHEET

### SECTION 12. ECOLOGICAL INFORMATION

#### 12.1. TOXICITY

##### 12.1.1. Acute (short-term) toxicity

##### For components

Substance (CAS Nr.)	Type	Value	Exposure time	Species	Organism	Method	Remark
benzyl alcohol (100-51-6)	LC <sub>50</sub>	460 mg/L	96 h	fish	<i>Pimephales promelas</i>		
	IC <sub>50</sub>	700 mg/L	72 h	algae	<i>Pseudokirchneriella subcapitata</i>	OECD 201	
	EC <sub>50</sub>	230 mg/L	48 h	crustacea	<i>Daphnia magna</i>	OECD 202	
	EC <sub>50</sub>	390 mg/L	24 h	bacteria			
3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)	EC <sub>10</sub>	1120 mg/L	18 h	bacteria	<i>Pseudomonas putida</i>		
	EC <sub>50</sub>	23 mg/L	48 h	crustacea	<i>Daphnia magna</i>	OECD 202	
	ErC <sub>50</sub>	> 50 mg/L	72 h	algae	<i>Scenedesmus subspicatus</i>		
	LC <sub>50</sub>	110 mg/L	96 h	fish	<i>Leuciscus idus</i>		
4,4'-methylenebis(cyclohexylamine) (1761-71-3)	LC <sub>50</sub>	> 100 mg/L	96 h	fish	<i>Leuciscus idus</i>		
	LC0	46 mg/L	96 h	fish	<i>Leuciscus idus</i>		
	EC <sub>50</sub>	6,84 mg/L	48 h	crustacea	<i>Daphnia magna</i>		
	EC <sub>50</sub>	140 – 200 mg/L	72 h	algae			
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	LC <sub>50</sub>	222 mg/L	24 h	fish	<i>Oncorhynchus mykiss</i>		
	LC100	240 mg/L	96 h	fish	<i>Oncorhynchus mykiss</i>		
	LC0	180 mg/L	96 h	fish	<i>Oncorhynchus mykiss</i>		
	EC <sub>50</sub>	718 mg/L	96 h	crustacea	<i>Palaemonetes</i>		
	EC <sub>100</sub>	1000 mg/L	96 h	crustacea	Neopanope		
	EC0	750 mg/L	96 h	crustacea	Neopanope		
	EC <sub>50</sub>	84 mg/L	72 h	algae	<i>Scenedesmus subspicatus</i>		
	NOEC	6,25 mg/L		algae			
methyleneoxide, polymer with benzenamine, hydrogenated (135108-88-2)	LC <sub>50</sub>	63 mg/L	96 h	fish	<i>Poecilia reticulata</i>		
	EC <sub>50</sub>	15,4 mg/L	48 h	crustacea	<i>Daphnia magna</i>		
	ErC <sub>50</sub>	43,9 mg/L	72 h	algae			
	EC <sub>50</sub>	187 mg/L	3 h	bacteria	Activated sludge		

## SAFETY DATA SHEET

### 12.1.2. Chronic (long-term) toxicity

#### For components

Substance (CAS Nr.)	Type	Value	Exposure time	Species	Organism	Method	Remark
benzyl alcohol (100-51-6)	NOEC	51 mg/l	21 days	crustacea	<i>Daphnia magna</i>	OECD 211	
3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)	NOEC	3 mg/l	21 days	crustaceans	<i>Daphnia magna</i>		
	NOEC	1,5 mg/l	72 h	algae	<i>Scenedesmus subspicatus</i>		
4,4'-methylenebis(cyclohexylamine) (1761-71-3)	NOEC	4 mg/l	504 h		<i>Daphnia</i>		
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	NOEC	6,25 mg/l		fish			

## 12.2. PERSISTENCE AND DEGRADABILITY

### 12.2.1. Abiotic degradation, physical- and photo-chemical elimination

No information.

### 12.2.2. Biodegradation

#### For components

Substance (CAS Nr.)	Type	Rate	Time	Evaluation	Method	Remark
benzyl alcohol (100-51-6)	biodegradability	95 %			OECD 301A/ ISO 7827/ EEC 92/69/V, C.4-A	
benzyl alcohol (100-51-6)	biodegradability	92 %			OECD 302 C	
3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)	biodegradability	8 %				

## 12.3. BIOACCUMULATIVE POTENTIAL

### 12.3.1. Partition coefficient

#### For components

Substance (CAS Nr.)	Media	Value	Temperature	pH	Concentration	Method
benzyl alcohol (100-51-6)	Octanol-water (log Pow)	1,05				
3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)	Octanol-water (log Pow)	0,99				

### 12.3.2. Bioconcentration factor (BCF)

#### For components

Substance (CAS Nr.)	species	Organism	Value	Duration	Evaluation	Method	Remark
benzyl alcohol (100-51-6)	BCF		1,37				

## 12.4. MOBILITY IN SOIL

### 12.4.1. Known or predicted distribution to environmental compartments

No information.

### 12.4.2. Surface tension

No information.

### 12.4.3. Adsorption/Desorption

No information.

## SAFETY DATA SHEET

### 12.5. RESULTS OF PBT AND VPVB ASSESSMENT

No evaluation.

### 12.6. OTHER ADVERSE EFFECTS

No information.

### 12.7. ADDITIONAL INFORMATION

#### For product

Harmful to aquatic life with long lasting effects.  
Do not allow to reach ground water, water courses or sewage system.

## SECTION 13. DISPOSAL CONSIDERATIONS

### 13.1. WASTE TREATMENT METHODS

#### 13.1.1. Product / Packaging disposal

##### Waste chemical

Add appropriate amount B component to component A and mix well. The reaction is exothermic. Leave at least 1 day - mixture should become hard. Classification number of hardened waste is 08 04 99. Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste. Dispose of in accordance with applicable waste disposal regulation.

##### Packaging

Dispose of in accordance with applicable waste disposal regulation. Deliver completely emptied containers to approved waste disposal authorities.

#### 13.1.2. Waste treatment-relevant information

-

#### 13.1.3. Sewage disposal-relevant information

-

#### 13.1.4. Other disposal recommendations

-

## SECTION 14. TRANSPORT INFORMATION

### 14.1. UN NUMBER

UN 2735

### 14.2. UN PROPER SHIPPING NAME

AMINES, LIQUID, CORROSIVE, N.O.S. (4,4'-isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine, 3-aminomethyl-3,5,5-trimethylcyclohexylamine)



### 14.3. TRANSPORT HAZARD CLASS(ES)

8

### 14.4. PACKING GROUP

III

### 14.5. ENVIRONMENTAL HAZARDS

NO.

### 14.6. SPECIAL PRECAUTIONS FOR USER

#### Limited quantities

5 L

## SAFETY DATA SHEET

---

**Tunnel restriction code**

(E)

**IMDG EmS**

F-A, S-B

**14.7. TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL AND THE IBC CODE**

Goods may not be carried in bulk in bulk containers, containers or vehicles.

## SECTION 15. REGULATORY INFORMATION

---

**15.1. SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE**

- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (including last amendment Commission Regulation (EU) 2015/830)

- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

15.1.1. Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-guideline)

Not applicable.

**15.2. CHEMICAL SAFETY ASSESSMENT**

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## SECTION 16. OTHER INFORMATION

---

Indication of changes

-

Abbreviations and acronyms

ATE - Acute Toxicity Estimate  
ADR - Agreement concerning the International Carriage of Dangerous Goods by Road  
ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
CEN - European Committee for Standardisation  
C&L - Classification and Labelling  
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008  
CAS# - Chemical Abstracts Service number  
CMR - Carcinogen, Mutagen, or Reproductive Toxicant  
CSA - Chemical Safety Assessment  
CSR - Chemical Safety Report  
DMEL - Derived Minimal Effect Level  
DNEL - Derived No Effect Level  
DPD - Dangerous Preparations Directive 1999/45/EC  
DSD - Dangerous Substances Directive 67/548/EEC  
DU - Downstream User  
EC - European Community  
ECHA - European Chemicals Agency  
EC-Number - EINECS and ELINCS Number (see also EINECS and ELINCS)  
EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway)  
EEC - European Economic Community  
EINECS - European Inventory of Existing Commercial Substances  
ELINCS - European List of notified Chemical Substances  
EN - European Standard  
EQS - Environmental Quality Standard  
EU - European Union  
Euphrac - European Phrase Catalogue  
EWC - European Waste Catalogue (replaced by LoW – see below)  
GES - Generic Exposure Scenario

## SAFETY DATA SHEET

---

GHS - Globally Harmonized System  
IATA - International Air Transport Association  
ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air  
IMDG - International Maritime Dangerous Goods  
IMSBC - International Maritime Solid Bulk Cargoes  
IT - Information Technology  
IUCLID - International Uniform Chemical Information Database  
IUPAC - International Union for Pure Applied Chemistry  
JRC - Joint Research Centre  
Kow - octanol-water partition coefficient  
LC<sub>50</sub> - Lethal Concentration to 50 % of a test population  
LD<sub>50</sub> - Lethal Dose to 50% of a test population (Median Lethal Dose)  
LE - Legal Entity  
LoW - List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)  
LR - Lead Registrant  
M/I - Manufacturer / Importer  
MS - Member States  
MSDS - Material Safety Data Sheet  
OC - Operational Conditions  
OECD - Organization for Economic Co-operation and Development  
OEL - Occupational Exposure Limit  
OJ - Official Journal  
OR - Only Representative  
OSHA - European Agency for Safety and Health at work  
PBT - Persistent, Bioaccumulative and Toxic substance  
PEC - Predicted Effect Concentration  
PNEC(s) - Predicted No Effect Concentration(s)  
PPE - Personal Protection Equipment  
(Q)SAR - Qualitative Structure Activity Relationship  
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006  
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail  
RIP - REACH Implementation Project  
RMM - Risk Management Measure  
SCBA - Self-Contained Breathing Apparatus  
SDS - Safety data sheet  
SIEF - Substance Information Exchange Forum  
SME - Small and Medium sized Enterprises  
STOT - Specific Target Organ Toxicity  
(STOT) RE - Repeated Exposure  
(STOT) SE - Single Exposure  
SVHC - Substances of Very High Concern  
UN - United Nations  
vPvB - Very Persistent and Very Bioaccumulative

### Key literature references and sources for data

-

### List of relevant H phrases

H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H373 May cause damage to organs through prolonged or repeated exposure .  
H412 Harmful to aquatic life with long lasting effects.



## SAFETY DATA SHEET

---

The information of this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under Section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.