



SAFETY DATA SHEET

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. PRODUCT IDENTIFIER

Product name

PARKETOLIT 1554A

chemius.net/VpHc7

1.2. RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST

Relevant identified uses

Adhesive for wood flooring - component A

Uses advised against

No information.

1.3. DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Manufacturer

MITOL, tovarna lepil, d.o.o., Sežana Address: Partizanska c. 78 Sežana, Slovenia

Phone: +386 5 73 12 300 Fax: +386 5 73 12 390 E-mail: lilijana.kocjan@mitol.si

Point of contact for safety info: Lilijana Kocjan Žorž

1.4. EMERGENCY TELEPHONE NUMBER

Emergency

112

Supplier

+386 5 73 12 300 (8:00-16:00)

SECTION 2. HAZARDS IDENTIFICATION

2.1 CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

Classification according to Regulation (EC) No 1272/2008 (CLP)

Skin Irrit. 2; H315 Causes skin irritation.

Skin Sens. 1A; H317 May cause an allergic skin reaction.

Eye Dam. 1; H318 Causes serious eye damage.

Aquatic Chronic 3; H412 Harmful to aquatic life with long lasting effects.



Revision: 20.2.2019

Creation date: 28.11.2014

Version: 2

SAFETY DATA SHEET

2.2 LABEL ELEMENTS

2.2.1. Labelling according to Regulation (EC) No 1272/2008 [CLP]





Signal word: Danger

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H412 Harmful to aquatic life with long lasting effects.

P102 Keep out of reach of children.

P273 Avoid release to the environment.

P280 Wear protective gloves/eye protection/face protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with national regulation.

2.2.2. Contains:

blocked polyisocyanate (CAS: 2155840-39-2) Cashew, nutshell liq. (CAS: 8007-24-7)

2.2.3. Special provisions

Special hazards are not known or expected.

2.3. OTHER HAZARDS

No information.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. SUBSTANCES

For mixtures see 3.2.



SAFETY DATA SHEET

3.2. MIXTURES

Name	EC according to Regulation (EC) No 1272/2008 (CLP)		Specific Conc. Limits	REACH Registration No.	
blocked polyisocyanate	2155840-39-2	5-10	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Irrit. 2; H315 Skin Sens. 1A; H317 Eye Dam. 1; H318		-
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700)	25068-38-6 500-033-5 603-074-00-8	5-10	Skin Irrit. 2; H315 Skin Sens. 1; H317 Eye Irrit. 2; H319 Aquatic Chronic 2; H411	Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 %	
hydrocarbons, C11-C12, isoalkanes, <2% aromatics	- 918-167-1 -	1-2,5	Flam. Liq. 3; H226 Asp. Tox. 1; H304 Aquatic Chronic 4; H413 EUH066		01-2119472146-39
hydrocarbons, C11-C13, isoalkanes, <2% aromatics	- 920-901-0 -	1-2,5	Asp. Tox. 1; H304 EUH066		01-2119456810-40
Cashew, nutshell liq.	8007-24-7	0,1-<1	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Irrit. 2; H315 Skin Sens. 1A; H317 Eye Dam. 1; H318		-

SECTION 4. FIRST AID MEASURES

4.1. DESCRIPTION OF FIRST AID MEASURES

General notes

When in doubt or if feeling unwell seek medical assistance. Show the safety data sheet and label to the physician.

Following inhalation

Remove patient to fresh air - move out of dangerous area. If symptoms occur, seek medical advice.

Following skin contact

Take off all contaminated clothing. Wash affected skin areas thoroughly with plenty of water and soap. If symptoms persist seek medical attention.

Following eye contact

Immediately flush eyes with running water, keeping eyelids apart. If irritation does not stop, seek professional medical treatment!

Following ingestion

Do not induce vomiting! Rinse mouth thoroughly with water. Rinse mouth with water and drink 2-3 dl water in sips. Consult a physician. Show the physician the safety data sheet or label.

4.2. MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

Inhalation

Excessive exposure to spray mist, fog, or vapours may cause respiratory irritation.

Skin contact

Itching, redness, pain.

May cause sensitisation by skin contact (symptoms: itching, redness, rashes).



SAFETY DATA SHEET

Eye contact

On contact with eyes causes serious damage.

Discomfort or pain, excessive blinking, lacrimation and redness, swelling of the conjunctiva.

Ingestion

Irritates mucous membranes in the mouth, throat, esophagus and in gastrointestinal area.

May cause nausea/vomiting and diarrhea.

May cause abdominal discomfort.

4.3. INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

-

SECTION 5. FIREFIGHTING MEASURES

5.1. EXTINGUISHING MEDIA

Suitable extinguishing media

Carbon dioxide. Dry chemical powder. Water spray. Alcohol resistant foam.

Unsuitable extinguishing media

_

5.2. SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

Hazardous combustion products

In the event of fire the following can be generated: carbon monoxide (CO), carbon dioxide (CO₂).

5.3. ADVICE FOR FIREFIGHTERS

Protective actions

In case of fire evacuate the area. In case of fire or heating do not breathe fumes/vapours. Cool containers at risk with water spray. If possible remove containers from endangered area.

Special protective equipment for firefighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (EN 137).

Additional information

Contaminated firefighting water must be disposed of in accordance with the regulations; do not allow to reach the sewage system.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

6.1.1. For non-emergency personnel

Protective equipment

Use personal protective equipment (Section 8).

Emergency procedures

Ensure adequate ventilation. No action shall be taken involving any personal risk or without suitable training. Prevent access to unprotected personnel. Do not breathe vapour or mist. Avoid contact with skin and eyes. Evacuate the danger zone.

6.1.2. For emergency responders

Use personal protective equipment.

6.2. ENVIRONMENTAL PRECAUTIONS

Do not allow product to reach water/drains/sewage systems or permeable soil. If accidental large entry into water or ground occurs, inform responsible authorities.



SAFETY DATA SHEET

6.3. METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

6.3.1. For containment

Limit spillages with non-combustible absorbents, e.g. sand, earth, vermiculite, diatomaceous earth.

6.3.2. For cleaning up

Absorb product (with inert material), collect it in special container and dispose it to a licensed hazardous-waste disposal contractor. Clean contaminated area with water and detergent.

6.3.3. Other information

_

6.4. REFERENCE TO OTHER SECTIONS

See also Sections 8 and 13.

SECTION 7. HANDLING AND STORAGE

7.1. PRECAUTIONS FOR SAFE HANDLING

7.1.1. Protective measures

Measures to prevent fire

Ensure adequate ventilation.

Measures to prevent aerosol and dust generation

_

Measures to protect the environment

-

7.1.2. Advice on general occupational hygiene

Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Avoid contact with skin and eyes. Do not breathe vapours/mist.

7.2. CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

7.2.1. Technical measures and storage conditions

Store in accordance with local regulations. Keep in cool and well ventilated area. Keep away from food, drink and animal feeding stuffs. Keep in well closed containers. Keep away from moisture and water. Storage temperature: +5 - 25 ° C.

7.2.2. Packaging materials

Store only in original container.

7.2.3. Requirements for storage rooms and vessels

Close opened containers after use. Put the containers upright to prevent from leaking.

7.2.4. Storage class

-

7.2.5. Further information on storage conditions

-

7.3. SPECIFIC END USE(S)

Recommendations

-

Industrial sector specific solutions

-



SAFETY DATA SHEET

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. CONTROL PARAMETERS

8.1.1. Occupational exposure limit values

No information.

8.1.2. Information on monitoring procedures

BS EN 14042:2003 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 482:2012+A1:2015 Workplace exposure. General requirements for the performance of procedures for the measurement of chemical agents. BS EN 689:2018 Workplace exposure. Measurement of exposure by inhalation to chemical agents. Strategy for testing compliance with occupational exposure limit values.

8.1.3. DNEL/DMEL values

For components

Name	Туре	Exposure route	Exposure frequency	Value	Remark
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) (25068-38-6)	Worker	dermal	short term (systemic effects)	8,3 mg/kg	
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) (25068-38-6)	Worker	inhalation	short term (systemic effects)	12,3 mg/m³	
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) (25068-38-6)	Worker	dermal	long term (systemic effects)	8,3 mg/kg	repeated
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) (25068-38-6)	Worker	inhalation	long term (systemic effects)	12,3 mg/m³	repeated
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) (25068-38-6)	Consumer	dermal	short term (systemic effects)	3,6 mg/kg	
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) (25068-38-6)	Consumer	inhalation	short term (systemic effects)	0,75 mg/m ³	
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) (25068-38-6)	Consumer	oral	short term (systemic effects)	0,75 mg/kg	
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) (25068-38-6)	Consumer	dermal	long term (systemic effects)	3,6 mg/kg	repeated
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) (25068-38-6)	Consumer	inhalation	long term (systemic effects)	0,75 mg/m ³	repeated
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) (25068-38-6)	Consumer	oral	long term (systemic effects)	0,75 mg/kg	repeated



SAFETY DATA SHEET

8.1.4. PNEC values

For components

Name	Exposure route	Value	Remark
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight $\leq 700) \ (25068\text{-}38\text{-}6)$	fresh water	0,006 mg/L	
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight $\leq 700) \ (25068\text{-}38\text{-}6)$	marine water	0,0006 mg/L	
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight $\leq 700) \ (25068\text{-}38\text{-}6)$	fresh water sediment	0,0005 mg/L	
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight $\leq 700) \ (25068\text{-}38\text{-}6)$	marine water sediment	0,00627 mg/kg	
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight $\leq 700)~(25068\text{-}38\text{-}6)$	water treatment plant	10 mg/L	
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight \leq 700) (25068-38-6)	soil	0,0478 mg/kg	

8.2. EXPOSURE CONTROLS

8.2.1. Appropriate engineering control

Substance/mixture related measures to prevent exposure during identified uses

Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Avoid contact with eyes and skin. Do not breathe vapours/aerosols. Avoid contact with skin, eyes and clothes.

Technical measures to prevent exposure

Provide good ventilation and local exhaust in areas with increased concentration.

8.2.2. Personal protective equipment

Eye and face protection

Safety glasses with side protection (EN 166).

Hand protection

Protective gloves (EN 374). Observe the manufacturer's instructions regarding the use, storage, maintenance and replacement of gloves. In case of damage or at the first signs of wear and tear, change the gloves immediately.

Skin protection

Cotton protective clothing and shoes that cover the entire foot (EN ISO 20345).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory protection. Protective masks (EN 136) or half masks (EN 140) with filter A (EN 14387).

Thermal hazards

8.2.3. Environmental exposure controls

_

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

-	Physical state:	liquid
-	Colour:	
-	Odour:	mild



SAFETY DATA SHEET

Important health, safety and environmental information

-	рН	No information.
-	Melting point/freezing point	No information.
-	Initial boiling point/boiling range	No information.
-	Flash point	No information.
-	Evaporation rate	No information.
-	Flammability (solid, gas)	No information.
-	Explosion limits (vol%)	No information.
-	Vapour pressure	No information.
-	Vapour density	No information.
-	Density	No information.
-	Solubility	No information.
-	Partition coefficient	No information.
-	Auto-ignition temperature	No information.
-	Decomposition temperature	No information.
-	Viscosity	No information.
-	Explosive properties	No information.
-	Oxidising properties	No information.

9.2. OTHER INFORMATION

- Remarks:

SECTION 10. STABILITY AND REACTIVITY

10.1. REACTIVITY

_

10.2. CHEMICAL STABILITY

Product is stable under normal conditions of use, recommended handling and storage conditions.

10.3. POSSIBILITY OF HAZARDOUS REACTIONS

-

10.4. CONDITIONS TO AVOID

No special precautions required. Consider the directions for use and storage.

10.5. INCOMPATIBLE MATERIALS

Strong oxidising agents.

10.6. HAZARDOUS DECOMPOSITION PRODUCTS

Under normal use conditions no hazardous decomposition products are expected. In case of fire/explosion vapours/gases that pose a health hazard are released.



SAFETY DATA SHEET

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. INFORMATION ON TOXICOLOGICAL EFFECTS

(a) Acute toxicity

Name	Exposure route	Туре	Species	Time	Value	Method	Remark
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) (25068-38-6)	oral	LD ₅₀	rat		15000 mg/kg		
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) (25068-38-6)	dermal	LD ₅₀	rabbit		> 23000 mg/kg		
hydrocarbons, C11-C12, isoalkanes, <2% aromatics (-)	oral	LD ₅₀	rat		> 5000 mg/kg		
hydrocarbons, C11-C12, isoalkanes, <2% aromatics (-)	dermal	LD ₅₀	rabbit		> 5000 mg/kg		
hydrocarbons, C11-C13, isoalkanes, <2% aromatics (-)	oral	LD ₅₀	rat		> 5000 mg/kg	OECD 401	
hydrocarbons, C11-C13, isoalkanes, <2% aromatics (-)	inhalation (vapours)	LC ₅₀	rat	8 h	> 5000 mg/l		
hydrocarbons, C11-C13, isoalkanes, <2% aromatics (-)	dermal	LD ₅₀	rabbit		> 5000 mg/kg		

(b) Skin corrosion/irritation

Name	Species	Time	Result	Method	Remark
blocked polyisocyanate (2155840-39-2)	rabbit		Irritating.		
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight \leq 700) (25068-38-6)			Irritating.		
Cashew, nutshell liq. (8007-24-7)	rabbit		Irritating.		
Additional information: Causes skin and eye irritation.					

(c) Serious eye damage/irritation

Name	Species	Time	Result	Method	Remark
blocked polyisocyanate (2155840-39-2)	rabbit		Corrosive.	OECD 405	
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight \leq 700) (25068-38-6)			Irritating.		
Cashew, nutshell liq. (8007-24-7)	rabbit		Corrosive.	OECD 405	
Additional information: Causes serious eye damage.					



SAFETY DATA SHEET

(d) Respiratory or skin sensitisation

Name	Exposure route	Species	Time	Result	Method	Remark
blocked polyisocyanate (2155840-39-2)	dermal	guinea pig		Sensitizing.	OECD 406	
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) (25068-38-6)	dermal			May cause sensitisation by skin contact.		
Cashew, nutshell liq. (8007-24-7)	dermal	guinea pig		Sensitizing.	OECD 406	

(e) (Germ cell) mutagenicity

Name	Туре	Species	Time	Result	Method	Remark
blocked polyisocyanate (2155840-39-2)	in-vitro mutagenicity	Human (lymphocytes)		Negative.	OECD 473	
blocked polyisocyanate (2155840-39-2)	in-vitro mutagenicity	Salmonella typhimurium		Negative.	OECD 471	Ames test
blocked polyisocyanate (2155840-39-2)	in-vitro mutagenicity	Cell: Mammalian-Animal		Negative.	OECD 476	
Cashew, nutshell liq. (8007-24-7)	in-vitro mutagenicity	Human (lymphocytes)		Negative.	OECD 473	
Cashew, nutshell liq. (8007-24-7)	in-vitro mutagenicity	Salmonella typhimurium		Negative.	OECD 471	Ames test
Cashew, nutshell liq. (8007-24-7)	in-vitro mutagenicity	Cell: Mammalian-Animal		Negative.	OECD 476	

(f) Carcinogenicity

No information.

(g) Reproductive toxicity

Name	Reproductive toxicity type	Туре	Species	Time	Value	Result	Method	Remark
blocked polyisocyanate (2155840- 39-2)	Effects on fertility	NOAEL (P)	rat	54 days	150 mg/kg		OECD 422	
blocked polyisocyanate (2155840-39-2)	Effects on fertility	NOAEL (F1)	rat	54 days	1000 mg/kg		OECD 422	
blocked polyisocyanate (2155840-39-2)	Maternal toxicity	NOAEL	rat	54 days	150 mg/kg		OECD 422	
blocked polyisocyanate (2155840-39-2)	Developmental toxicity	NOAEL	rat	54 days	1000 mg/kg		OECD 422	
Cashew, nutshell liq. (8007-24-7)	Effects on fertility	NOAEL (P)	rat	54 days	150 mg/kg		OECD 422	
Cashew, nutshell liq. (8007-24-7)	Effects on fertility	NOAEL (F1)	rat	54 days	1000 mg/kg		OECD 422	
Cashew, nutshell liq. (8007-24-7)	Maternal toxicity	NOAEL	rat	54 days	150 mg/kg		OECD 422	
Cashew, nutshell liq. (8007-24-7)	Developmental toxicity	NOAEL	rat	54 days	1000 mg/kg		OECD 422	

Summary of evaluation of the CMR properties

No information.

(h) STOT-single exposure

No information.



SAFETY DATA SHEET

(i) STOT-repeated exposure

Name	Exposure route	Туре	Species	Time	Organ	Value	Result	Method	Remark
blocked polyisocyanate (2155840-39-2)	oral	NOAEL	rat	54 days		150 mg/kg		OECD 422	
Cashew, nutshell liq. (8007-24-7)	oral	NOAEL	rat	54 days		150 mg/kg		OECD 422	

(j) Aspiration hazard

No information.



SAFETY DATA SHEET

SECTION 12. ECOLOGICAL INFORMATION

12.1. TOXICITY

12.1.1. Acute (short-term) toxicity

For components

Substance (CAS Nr.)	Туре	Value	Exposure time	Species	Organism	Method	Remark
blocked polyisocyanate (2155840-39-2)	LL50	> 1000 mg/L	96 h	fish	Cyprinodon variegatus	OECD 203	
	LL ₅₀	> 1000 mg/L	48 h	Daphnia	Acartia tonsa		
	EL ₅₀	250 mg/L	72 h	algae	Skeletonema costatum		ISO 10253
	EC ₅₀	> 1000 mg/L	3 h	bacteria	Activated sludge	OECD 209	
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) (25068-	EC ₅₀	1,8 mg/L	48 h	crustacea	Daphnia magna		
38-6)	EC ₅₀	11 mg/L	72 h	algae	Selenastrum capricornutum		
	LC ₅₀	2 mg/L	96 h	fish	Oncorhynchus mykiss		
	EC ₅₀	> 42,6 mg/L	8 h	bacteria			
hydrocarbons, C11-C12, isoalkanes, <2% aromatics (-)	LL ₀	1000 mg/L	96 h	fish	Oncorhynchus mykiss		
	EL ₀	1000 mg/L	48 h	crustacea	Daphnia magna		
	EL ₀	1000 mg/L	72 h	algae	Pseudokirchneriella subcapitata		
	NOELR	1000 mg/L	72 h	algae	Pseudokirchneriella subcapitata		
hydrocarbons, C11-C13, isoalkanes, <2% aromatics (-)	LL ₀	1000 mg/L	96 h	fish	Oncorhynchus mykiss		
	EL ₀	1000 mg/L	48 h	crustacea	Daphnia magna		
	EL ₀	1000 mg/L	72 h	algae	Pseudokirchneriella subcapitata		
	NOELR	1000 mg/L	72 h	algae	Pseudokirchneriella subcapitata		
Cashew, nutshell liq. (8007-24-7)	LL50	> 1000 mg/L	96 h	fish	Cyprinodon variegatus	OECD 203	
	LL ₅₀	> 1000 mg/L	48 h	Daphnia	Acartia tonsa		
	EL ₅₀	250 mg/L	72 h	algae	Skeletonema costatum		ISO 10253
	EC ₅₀	> 1000 mg/L	3 h	bacteria	Activated sludge	OECD 209	



SAFETY DATA SHEET

12.1.2. Chronic (long-term) toxicity

For components

Substance (CAS Nr.)	Туре	Value	Exposure time	Species	Organism	Method	Remark
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) (25068-38-6)	NOEC	0,3 mg/l	21 days	crustaceans	Daphnia magna		

12.2. PERSISTENCE AND DEGRADABILITY

12.2.1. Abiotic degradation, physical- and photo-chemical elimination

No information.

12.2.2. Biodegradation

For components

Substance (CAS Nr.)	Туре	Rate	Time	Evaluation	Method	Remark
blocked polyisocyanate (2155840-39-2)	-			not readily biodegradable		
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) (25068-38-6)	biodegradability	12 %	28 days		OECD 302 B/ISO 9888/EEC 92/69/V, C.9	
hydrocarbons, C11-C12, isoalkanes, <2% aromatics (-)	biodegradability	31,3 %	28 days			
hydrocarbons, C11-C13, isoalkanes, <2% aromatics (-)	biodegradability	31,3 %	28 days			
Cashew, nutshell liq. (8007-24-7)	biodegradability	96 %	28 days		OECD 301 D	

12.3. BIOACCUMULATIVE POTENTIAL

12.3.1. Partition coefficient

For components

Substance (CAS Nr.)	Media	Value	Temperature	рΗ	Concentration	Method
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) (25068-38-6)	Octanol-water (log Pow)	3,242	25 °C			

12.3.2. Bioconcentration factor (BCF)

For components

Substance (CAS Nr.)	species	Organism	Value	Duration	Evaluation	Method	Remark
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average molecular weight ≤ 700) (25068-38-6)	BCF		100 – 3000				

12.4. MOBILITY IN SOIL

12.4.1. Known or predicted distribution to environmental compartments

No information.

12.4.2. Surface tension

No information.

12.4.3. Adsorption/Desorption

For components

Substance (CAS Nr.)	Туре	Criterion	Value	Evaluation	Method	Remark
reaction product: bisphenol-A-(epichlorhydrin), epoxy resin (number average	Soil	log KOC				
molecular weight ≤ 700) (25068-38-6)			2000			



SAFETY DATA SHEET

Creation date: 28.11.2014 Revision: 20.2.2019 Version: 2

12.5. RESULTS OF PBT AND VPVB ASSESSMENT

No evaluation.

12.6. OTHER ADVERSE EFFECTS

No information.

12.7. ADDITIONAL INFORMATION

For product

Harmful to aquatic life with long lasting effects.

Do not allow to reach ground water, water courses or sewage system.

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. WASTE TREATMENT METHODS

13.1.1. Product / Packaging disposal

Waste chemical

Dispose of in accordance with applicable waste disposal regulation. Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste.

Packaging

Dispose of in accordance with applicable waste disposal regulation. Deliver completely emptied containers to approved waste disposal authorities.

13.1.2. Waste treatment-relevant information

-

13.1.3. Sewage disposal-relevant information

-

13.1.4. Other disposal recommendations

SECTION 14. TRANSPORT INFORMATION

14.1. UN NUMBER

Not applicable.

14.2. UN PROPER SHIPPING NAME

ADR, RID, IMDG, ADN, IATA: Not dangerous according to transport regulations.

14.3. TRANSPORT HAZARD CLASS(ES)

Not applicable.

14.4. PACKING GROUP

Not applicable.

14.5. ENVIRONMENTAL HAZARDS

NO.

14.6. SPECIAL PRECAUTIONS FOR USER

Not applicable.

14.7. TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL AND THE IBC CODE

Not applicable.



Creation date: 28.11.2014 Revision: 20.2.2019

Version: 2

SAFETY DATA SHEET

SECTION 15. REGULATORY INFORMATION

15.1. SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE SUBSTANCE **OR MIXTURE**

- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (including last amendment Commission Regulation (EU) 2015/830)
- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

15.1.1. Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-guideline)

Not applicable.

15.2. CHEMICAL SAFETY ASSESSMENT

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16. OTHER INFORMATION

Indication of changes

Abbreviations and acronyms

- ATE Acute Toxicity Estimate
- ADR European Agreement concerning the International Carriage of Dangerous Goods by Road
- ADN European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
- CEN European Committee for Standardisation
- C&L Classification and Labelling
- CLP Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
- CAS# Chemical Abstracts Service number
- CMR Carcinogen, Mutagen, or Reproductive Toxicant
- CSA Chemical Safety Assessment
- CSR Chemical Safety Report
- DMEL Derived Minimal Effect Level
- DNEL Derived No Effect Level
- DPD Dangerous Preparations Directive 1999/45/EC
- DSD Dangerous Substances Directive 67/548/EEC
- DU Downstream User
- EC European Community
- ECHA European Chemicals Agency
- EC-Number EINECS and ELINCS Number (see also EINECS and ELINCS)
- EEA European Economic Area (EU + Iceland, Liechtenstein and Norway)
- EEC European Economic Community
- EINECS European Inventory of Existing Commercial Substances
- ELINCS European List of notified Chemical Substances
- EN European Standard
- EQS Environmental Quality Standard
- EU European Union
- Euphrac European Phrase Catalogue
- EWC European Waste Catalogue (replaced by LoW see below)
- GES Generic Exposure Scenario
- GHS Globally Harmonized System
- IATA International Air Transport Association
- ICAO-TI Technical Instructions for the Safe Transport of Dangerous Goods by Air
- IMDG International Maritime Dangerous Goods
- IMSBC International Maritime Solid Bulk Cargoes
- IT Information Technology
- IUCLID International Uniform Chemical Information Database
- IUPAC International Union for Pure Applied Chemistry
- JRC Joint Research Centre



SAFETY DATA SHEET

Kow - octanol-water partition coefficient

LC₅₀ - Lethal Concentration to 50 % of a test population

LD₅₀ - Lethal Dose to 50% of a test population (Median Lethal Dose)

LE - Legal Entity

LoW - List of Wastes (see http://ec.europa.eu/environment/waste/framework/list.htm)

LR - Lead Registrant

M/I - Manufacturer / Importer

MS - Member States

MSDS - Material Safety Data Sheet

OC - Operational Conditions

OECD - Organization for Economic Co-operation and Development

OEL - Occupational Exposure Limit

OJ - Official Journal

OR - Only Representative

OSHA - European Agency for Safety and Health at work

PBT - Persistent, Bioaccumulative and Toxic substance

PEC - Predicted Effect Concentration

PNEC(s) - Predicted No Effect Concentration(s)

PPE - Personal Protection Equipment

(Q)SAR - Qualitative Structure Activity Relationship

REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006

RID - Regulations concerning the International Carriage of Dangerous Goods by Rail

RIP - REACH Implementation Project

RMM - Risk Management Measure

SCBA - Self-Contained Breathing Apparatus

SDS - Safety data sheet

SIEF - Substance Information Exchange Forum

SME - Small and Medium sized Enterprises

STOT - Specific Target Organ Toxicity

(STOT) RE - Repeated Exposure

(STOT) SE - Single Exposure

SVHC - Substances of Very High Concern

UN - United Nations

vPvB - Very Persistent and Very Bioaccumulative

Key literature references and sources for data

_

List of relevant H phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

EUH066 Repeated exposure may cause skin dryness or cracking.

The information of this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under Section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.



SAFETY DATA SHEET